

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION E. SW Cor. Sec. 31 (NW cor S. 6, 30-9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7376)

-----

Set post cor. tps. 29, and 30 S., Rgs. 9 and 10 W., from which

- A Fir 30" dia., bears N.89½°W., 244 lks. dist.
- A Fir 30" dia., bears S.83°W., 210 lks. dist.
- A Rock 5 ft. dia. and 4 ft. high bears N.68°E., 28 lks. dist. (marked X)
- A Rock 2 ft. high and 1 ft. by 3 ft. at surface of ground, bears S.70°E., 20 lks. dist. (marked X)

GLO resurvey by William M. Porter, Deputy Surveyor, Under Special Instructions dated June 5, 1907, Independent of, but in connection with his contract #768, dated March 8, 1907 - (DCSO records Vol. 31 Page(s) 13013 and 13014)

-----

(Page 13013)

The established corner of Tps. 29 and 30 S., R. 9 W., which is a stone 32 x 32 x 18 ins., above ground, firmly set and marked with 6 notches on S. and E. faces, from which

- A rock 5 ft. dia., 4 ft. high, bears N.68°E., 28 lks. dist. mkd. with an X.
- A Fir 30" dia., bears S.83°W., 230 lks. dist. mkd. T30S R10W S1 BT.
- A Fir 30" dia., bears N.89½°W., 244 lks. dist. mkd. T29S R10W S36 BT.

A rock 3x2x1 ft. above ground, S.70°E., 20 lks. mkd. X.

Notes of above cor. not fully agreeing with notes furnished by the surveyor general, but nearly so.

(Page 13014)

Complying with instructions contained in letter "E" dated April 29, 1909, from the Hon. Commissioner of the GLO on July 16, 1909, I returned to the field and have made the following amendments in connection with my surveys in T29S R9W, under special instructions dated June 5, 1907, independent of, but in connection with my Cont. #768, dated March 8, 1907, viz: At the cor. of Tps. 29 and 30 S., R9W, on the E. bdy. Sec. 1, T30S R10W., established by Hathorn as common to four townships, cannot properly refer to the township on the West, I Obliterate the markings on the SW. and NW. bearing trees for this corner and change the markings on corner stone to read as follows:

- T29S on N., R9W on E., and T30S on S. face; with 6 notches on S. and E. edges.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION E. SW Cor. Sec. 31; (NW cor. S. 6, T30-9)

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

Survey by Bruce A. Shaner - For: Evans Products Co. - Jan/April 1963 - RM 1-36

-----

Hathorn's corner, Found:  
 32" x 32" x 18" stone mkd. "CO" with 6 notches on both S. and E. sides.  
 I set a nail, from which  
 An X on 2' x 1' x 3' rock bears S.70°E., 14.7 ft. (Rec. 13.2 ft.)  
 An X on 4' x 5' rock, also scribed "BO" bears N.68°E., 18.5 ft.

BLM Resurvey by Jack W. Bowder; John P. Farnsworth; Wayne L. Rogers, Cadastral Surveyors, Group #'s 976; #1000; #996; #1091, surveyed May 1979/Sept. 1982 - (DCSO records Vol. 44 Page(s) 17078-79)

-----

The cor. of Tps. 29 and 30 S., R 9 W., on the E. bdy. of T30S R10W., recovered and recorded by Shaner in 1963, monumented with the original sandstone, 32 x 32 ins., firmly set, projecting 18" above ground with chisel marks 30S and 6 grooves on S., 29S and 6 grooves on N., and CC on E. faces, from which the original bearing objects:  
 A sandstone 5 x 5 x 4 ft. above ground bears N.68°E., 28 lks. dist. with marks X BO visible.  
 A sandstone 3 x 2 x 1 ft. above ground bears S.70°E., 22 lks. dist. with marks X BO visible.

At the corner point  
Set a brass tablet, 3¼" dia., 3 1/2" stem, in drill hole in corner stone mkd:

		T 29 S
		R 9 W
T 30 S		S 31
R 10 W		S 6
S 1		T 30 S
		1979

from which  
A Fir 20" dia., bears S.52°E., 19 lks. dist. mkd. T30S R9W S6 BT.

Survey by Ronald Geisler, LS #1988 - For: Champion International - July 1986 - C.S. File 63/34-35

-----

Found - 1979 BLM 3½" brass cap on a 1" I.P., set in drill hole in orig. 32" x 32" x 18" stone.  
 Bearing object, rock 5 ft. dia., 4 ft. high, bears N.68°E., 18.5 ft. Marks visible. (Orig.)  
 (Cont. Next Page)

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 100100

PRIMARY CORNER DESCRIPTION E SW Cor. Sec. 31; NW Cor S. 6, T30-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Bearing object, rock 3 ft. x 2 ft. x 1 ft. above  
ground, bears S.70°E., 14.5 ft. (Rec. 13.2 ft.)  
Marks visible. (Orig.)  
20" Fir now stump, bears S.52°E., 12.5 ft., healed  
face. (1979)