

PRIMARY CORNER DESCRIPTION NE. Cor. Sec. 1, T30S R10W

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by William M. Porter, Deputy Surveyor, Under Special Instructions dated June 5, 1907, Independent of, but in connection with his contract #768, dated March 8, 1907 - (DCSO records Vol. 31 Page(s) 13014)

-----  
(North, 2.00 chs. from NW Cor. Sec. 6, T30S R9W)  
Set basalt stone 22 x 17 x 6 ins., 16½" in the ground for NE. cor. sec. 1, T30S R10W., marked with 6 notches on S. and W. edges; from which  
A Myrtle tree, 4" dia., bears S.64°W., 15 lks. dist. mkd. T30S R10W S1 BT.

Survey by Bruce A. Shaner - For: Evans Products Co. - Jan/April 1963 - RM 1-36

-----  
Porter's corner - Found:  
A Rock with 6 notches on S. side and 7 notches on W. side. I set a nail, from which a:  
6" Chinquapin BT, (Rec. Myrtle) bears S.64°W., 9.9 ft. (old face is all rotted out)  
18" D.Fir, I scribed "S1 T30S R10W BT", S.38°W., 34.0 ft.

BLM Resurvey by Jack W. Bowder; John P. Farnsworth; Wayne L. Rogers, Cadastral Surveyors, Group #'s 976; #1000; #996; #1091, surveyed May 1979/Sept. 1982 - (DCSO records Vol. 44 Page(s) 17079)

-----  
The NE. cor. of T30S R10W., perpetuated and recorded by Shaner in 1963, monumented with the original sandstone 22 x 17 x 6 ins., firmly set, projecting 10" above ground, mkd. with 6 grooves on the S. and W. faces, from which a bearing tree mkd. by Shaner

A Fir 20" dia., bears S.33°W., 52 lks. with healed blaze. and bearing trees mkd. by person(s) unknown

A Chinquapin 6" dia., bears S.70°W., 15 lks. dist., no marks visible on decayed blaze.

A Fir 19" dia., bears S.87½°W., 34 lks. with healed blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 29 S R 9 W  
S 31  
-----  
T 30 S |  
R 10 W |  
S 1

1979

Deposit corner stone alongside iron post.

(Cont. Next Page)

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 100102

PRIMARY CORNER DESCRIPTION NE. Cor. Sec. 1, T30S R10W

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

Survey by Ronald Geisler, LS #1988 - For: Champion International - July 1986 - C.S. File 63/34-48

-----

Found - 1979 BLM 3½" brass cap on a 2" I.P. extends 1" above ground.

Corner stone found alongside monument.

6" Myrtle now down decayed and out of position.

Blazed face with BT tag visible. (date unknown)

19" D.Fir now stump, bears N.87½°W., (Rec. S.87½°W.)  
healed face, 22.4 ft. (date unknown)

21" D.Fir bears S.38°W., 34.3 ft. Healed face.  
(1963)