

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO resurvey by William M. Porter, Deputy Surveyor, Under contract #768, dated March 8, 1907 - (DCSO records Vol. 16 Page(s) 6642)

Set a basalt stone 11x11x8 ins., 8" in ground mkd. ¼ on W. face, from which
A Hemlock 10" dia., bears S.87°E., 50 lks. mkd. ¼ S22 BT
A Hemlock 15" dia., bears N.87°W., 40 lks. mkd. ¼ S21 BT

BLM remonumentation of corner by Jack W. Bowder, Cadastral Surveyor, under Group #350, Surveyed Nov. 1977/March 1978 - (DCSO records Vol. 42 Page(s) 16420)

The ¼ sec. cor. monumented with the original basalt stone 11 x 11 x 8 ins., firmly set 11" in the ground mkd. ¼ on W. face, from which the remains of an original bearing tree:

A Hemlock stump 20" dia., bears N.87°W., 16 lks. dist., no marks visible. (Rec. 40 lks.)

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 29 S R 9 W
1/4
S 21 | S 22
1978

from which new bearing trees:

A Fir 5" dia., bears N.65°E., 26 lks. dist., mkd. ¼ S22 BT.

A Fir 4" dia., bears N.38°W., 16½ lks. dist. mkd. X BT.
Deposit corner stone alongside iron post.

Fd. OK, Sept. 1996 by J. Minor - M 125-76

Douglas Co. Surveyors Office - Randall Smith and Stephen Flause, crew - Oct. 22, 1996 - C.S. File 65/9-29

Found - 3¼" BLM brass cap on a 2½" O.D. Iron pipe, protruding 5" above ground (1978 BLM)

A probe of area around BC/IP was made, a stone was found along West edge of BC/IP approx. 4" below ground. Stone was not dug out. (orig. stone)

4" now 9" dia. D.Fir with a fully healed blaze, bears N.38°W., 10.9 ft. to center of root crown (agrees w/rec) Record per 1996 J. Minor survey is N.44°W., 10.5 ft., fits well with center of trunk. BT is a pistol butt.

No other BTs were found.

(Cont. Next Page)

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 400340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 21 and 22

Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____
Alias_____	Description_____

New BTs- 11" dia. Hemlock double blazed and scribed "¼ S21 CS BT" bears S.79°W., 28.4 ft.
8" dia. D.Fir double blazed and scribed "¼ S21 CS BT" bears S.53°W., 14.2 ft. to center of root crown.
4" dia. D.Fir double blazed and scribed "X BT" bears S.9½°E., 13.6 ft.
A large slide is northwesterly of corner.

BLM Dependent resurvey by Joseph J Johnson, Cadastral Surveyor under Group #2864, surveyed Feb. 2017/Oct. 2018 - (DCSO Records Vol. 59 Page(s) 23396)

The ¼ sec. cor of secs. 21 & 22, perpetuated by Douglas Co. Surveyor's Office in 1996, monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with a brass cap (properly) mkd.
from which a bearing tree mkd. by Bowder in 1978
A fir, 20" dia., bears N.46¾°W., 10.9 ft., with a healed blaze. (Record, bears N.38°W.)
and the BTs mkd. by Douglas County Surveyor's Office
A fir, 9" dia., bears S.9°E., 14.0 ft., with a healed double blaze.
A fir, 10" dia., bears S.50½°W., 15.4 ft., with a healed blaze.
A hemlock, 13" dia., bears S.77¾°W., 27.9 ft., with a healed blaze.