

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO resurvey by William M. Porter, Deputy Surveyor, Under contract #768, dated March 8, 1907 - (DCSO records Vol. 16 Page(s) 6643)

Dead Fir 48" dia., for cor. of secs. 15, 16, 2 and 22, marked T29S S15 on NE.; R9W S22 on SE.; S21 on SW.; and S16 on NW. faces, with three notches on S. and E. sides, from which

- A Hemlock 8" dia., bears N.23°E., 80 lks. mkd. T29S R9W S15 BT.
- A Hemlock 36" dia., bears S.65°E., 27 lks. mkd. T29S R9W S22 BT.
- A Hemlock 38" dia., bears S.38°W., 42 lks. mkd. T29S R9W S21 BT.
- A Fir 50" dia, bears N.43°W., 40 lks. mkd. T29S R9W S16 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Sept. 1959 - C.S. File 49/100-49

Found - Orig. corner tree, now down and mostly rotted, shows scribe marks "S"

- Orig. 38" now 40" Hemlock snag, shows good scribing, "T29S R9W S21 BT", S.38°W., 27.7 ft.
- Orig. 50" now 50" Fir snag, N.43°W., 20 ft., record N.43°W., 26.4 ft., shows good scribing "T29S".

No trace of original NE. or SE. BTs found.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R 9 W			
Coos Co.	S 16	S 15	Doug Co
	S 21	S 22	
1959			

New BTs-

- 10" R.Fir bears S.63°W., 9.8 ft. scribed S21 T29S R9W DCS BT.
- 11" R.Fir bears S.15°E., 16.5 ft. scribed S22 T29S R9W DCS BT.
- 11" R.Fir bears N.38°W., 41.5 ft. scribed S16 T29S R9W DCS BT.
- 10" R.Fir bears N.68°E., 44.2 ft. scribed S15 T29S R9W DCS BT.

Fd. and Used in BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #606, surveyed May\June 1968 (DCSO records Vol. 35 Page(s) 14399-40)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM retracement by George M. Winter, Cadastral Surveyor, under Group No. 2500, OR Admin file No. 1302, surveyed March/May 2013 - (DCSO Records BLM Plat T29-9 2014-1)

The cor. of secs. 15, 16, 21, and 22, perpetuated by the Douglas County Surveyor's Office in 1959, monumented with on iron post, 1¼" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.

from which the remains of an original BT

A decayed stump, 42" dia., bears N.43°W., 19.8 ft., with no marks visible.

and the remains of BTs mkd by the Douglas Co Surveyors Office

A fir, 30" dia., bears N.68°E., 44.2 ft., with a healed blaze.

A fir snag, 26" dia., bears S.15°E., 16.5 ft., with a healed blaze.

A fir, 27" dia., bears S.63°W., 9.9 ft., with a healed blaze.

A decayed fir stump, 22" dia., bears N.39°W., 40.9 ft., with no marks visible. (Record, N.37°W.)

and new reference monuments

A steel reinforcing rod, 30" long, 5/8" dia., driven 27" in the ground, bears S.2°57'15" E., 27.0 ft., with an aluminum cap mkd. RM T29S R9W S22 27.0 FT TO COR 2013 and an arrow pointing to the cor.

A steel reinforcing rod, 30" long, 5/8" dia., driven 25" in the ground, bears N.53°00'56"W., 25.0 ft., with an aluminum cap mkd. RM T29S R9W S16 25.0 FT TO COR 2013 and an arrow pointing to the cor.

BLM Dependent resurvey by Joseph J Johnson, Cadastral Surveyor under Group #2864, surveyed Feb. 2017/Oct. 2018 - (DCSO Records Vol. 59 Page(s) 23696-7)

The cor. of secs. 15, 16, 21, & 22, monumented with an iron post, 1¼" dia., firmly set, projecting 14" above ground, with a brass cap (properly) mkd

from which the remains of an original bearing tree

A decayed fir stump, 39" dia., bears N.43°W., 19.8 ft., no marks visible.

and the remains of the BTs mkd. by Byron, in 1959, reported by Winter in 2013

A fir, 30" dia., bears N.68°E. 44.2 ft., with a healed blaze.

A fir snag, 27" dia., bears S.15°E., 16.5 ft., with a healed blaze.

A fir, 28" dia., bears S.63°W., 9.9 ft. with a healed blaze.

Continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 400400

PRIMARY CORNER DESCRIPTION Sec. Cor. for 15, 16, 21 and 22

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A decayed fir stump, 23" dia., bears N.39°W., 40.9 ft., no marks visible.
and the reference monuments set by Winter in 2013
An iron rod, 5/8" dia., firmly set, projecting 4" above ground, bears S.2°51'59"E., 27.17 ft., (Record, S.2°57'15"E., 27.0 ft.) with an aluminum cap mkd. RM T29S R9W S22 27.0 FT TO COR 2013 and an arrow pointing to the cor.
An iron rod, 5/8" dia. firmly set, projecting 5" above ground, bears N.53°00'56"W. 25.46 ft., (Record 25.0 ft) with an aluminum cap mkd. RM T29S R9W S16 25.0 FT TO COR 2013 and an arrow pointing to the cor.