

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO resurvey by William M. Porter, Deputy Surveyor, Under contract #768, dated March 8, 1907 - (DCSO records Vol. 16 Page(s) 6645)

-----  
Set a Cedar post 3 ft. long, 3" sq., 24" in ground, for ¼ sec. cor. marked ¼ S16 on W. and 15 on E. faces, from which  
A Cedar 5" dia., bears S.45°E., 15 lks. mkd. ¼ S15 BT.  
A Hemlock 5" dia., bears S.30°W., 6 lks. mkd. ¼ S16 BT.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #606, surveyed May\June 1968 (DCSO records Vol. 35 Page(s) 14400)

-----  
Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼  
S 16 | S 15  
T 29 S R 9 W  
1968

from which

A Fir 10" dia., bears S.57°E., 11 lks. mkd. ¼ S15 BT.  
A Fir 7" dia., bears N.49°W., 15½ lks. mkd. ¼ S16 BT

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2092, surveyed Sept. 2004 - May 2005 - (DCSO records Vol. 56 Page(s) 22243-4)

-----  
The ¼ sec. cor. of secs. 15 and 16, monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Peterson

A fir, 18" dia., bears S.57°E., 7.3 ft with a healed blaze  
A fir snag, 9" dia., bears N.49°W., 10.2 ft., with a healed blaze.

and a new bearing tree

A hemlock, 5" dia., bears N.14°W., 30.8 ft., mkd. X BT.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

The geographic positions (NAD 1983 (CORS)) of the following corners were determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System stations noted above ("CAPE BLANCO CORS ARP" & "DODSON BUTTE CORS ARP")

Latitude: 43°02'49.20"N.; Longitude: 123°45'41.14"W.

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 400440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 15 and 16

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM retracement by George M. Winter, Cadastral Surveyor, under Group No. 2500, OR Admin file No. 1302, surveyed March/May 2013 - (DCSO Records BLM Plat T29-9 2014-1)

-----  
The ¼ sec. cor. of secs. 15 and 16, monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with brass cap (properly) mkd.

from which the remains of bearing trees mkd. by Peterson

A fir, 19" dia., bears S.57°E., 7.3 ft., with a healed blaze.

A fir snag, 8" dia., bears N.49°W., 10.2 ft., with a healed blaze.

and a bearing tree mkd. by Skeesick in 2004-2005

A hemlock, 8" dia., bears N.14°W., 30.8 ft., with a healed double blaze.

NAD 1983 (2011)

Latitude - 43°02'49.200"N. Longitude 123°45'41.139"W.