

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9 & 10 only (South)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. S. Champman, Deputy Surveyor, under Contract #234, dated June 24, 1875 - (DCSO records Vol. 16 Page 6630)

Set post 4 ft. long, 5" dia., one ft. in ground for cor. of secs. 9, 10, 15 and 16, from which
A Hemlock 10" dia., bears N.52°W., 24 lks.
A Hemlock 18" dia., bears N.40°E., 22 lks.
A Cedar 14" dia., bears S.62°E., 23 lks.
A Hemlock 30" dia., bears S.45°W., 11 lks.

GLO resurvey by William M. Porter, Deputy Surveyor, Under Special Instructions dated June 5, 1907, Independent of, but in connection with his contract #768, dated March 8, 1907 - (DCSO records Vol. 16 Page(s) 6641)

The cor established for secs 9, 10, 15 & 16 which agrees with the notes furnished by the surveyor general. Destroy all markings on post and witness trees referring to secs. 15 & 16

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #606 surveyed May/June 1968 (DCSO recs Vol 35 Pg 14399)

Pt for the cor. of secs.9 & 10 only, at proportionate dist; there is no remaining evidence of the original corner.
Set an iron post 28" long, 2½" dia., 24" in the ground, with brass cap marked: T 29 S R 9 W
 S 9 | S 10
 S 16
 1968

from which
A burned Fir stump 35" dia. bears N.63°E. 23 lks mkd. T29S R9W S10 BT.
A Fir 56" dia., bears N.38°W., 70 lks mkd. T29S R9W S9 BT.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2092, surveyed Sept. 2004 - May 2005 - (DCSO records Vol. 56 Page(s) 22245)

The cor. of secs. 9 & 10 only, bears N.89°04'33"W., 35.70 ft. (from the CC Secs. 15 & 16) monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd.
from which the remains of bearing trees mkd. by Peterson
A burned, decayed hemlock snag, 31" dia., bears N.63°E., 15.2 ft., with scribe marks T29S R9W S10 BT visible on an open blaze. (Record, fir stump)

continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 400500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 9 & 10 only (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A burned, fir snag, 54" dia., bears N.38°W., 46.2 ft., with scribe marks 9S R9W S9 BT visible on an open blaze.
and new bearing trees
A fir, 8" dia., bears N.79½°E., 19.5 ft., mkd. T29S R9W S10 BT.
A fir, 9" dia. bears N.61½°W. 13.1 ft. mkd. T29S R9W S9 BT

Fd. OK by K DeGroot, 11/2011 - C.S. file 65/75-7