

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. S. Champman, Deputy Surveyor, under Contract #234, dated June 24, 1875 - (DCSO records Vol. 16 Page(s) 6630-31)

Set post 4 ft. long, 4" dia., one ft. in ground for ¼ sec. cor., from which
 A Cedar 24" dia., bears N.50°W., 14 lks.
 A Hemlock 10" dia., bears S.83°E., 15 lks.

J. N. Gearhart - Wit: M.S. Hubbard; Jack Densler - June 1950 - C.S. File 40/253

At the ¼ cor., I find the Cedar bearing tree, N.50°00'E., 14 lks. to be a snag. No sign of the Hemlock BT, S.83°00'E., 15 lks.. I mark a R.Cedar 30" dia., "¼ S10 BT 1743" bearing S.16°00'E., 15.5 ft. distant. (Rec. for Cedar is NW)

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #606, surveyed May\June 1968 (DCSO records Vol. 35 Page(s) 14401)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
 Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

¼
 S 9 | S 10
 T 29 S R 9 W
 1968

from which
 A Cedar 14" dia., bears S.75°E., 183 lks. dist. mkd. ¼ S10 BT.
 A Hemlock 9" dia., bears S.79°W., 161 lks. dist. mkd. ¼ S9 BT.

Found OK by W. Rogers, Mar. 2001 - M136-62 A & B

BLM retracement by Aaron M Graham, Cadastral Surveyor, under Group No 2300, surveyed Oct. 2007 - (DCSO records Vol. 56 Page(s) 22255 and BLM Plat 2010-3)

The ¼ sec. cor. of secs. 9 & 10, monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with brass cap (properly) mkd.
 from which the BTs mkd by Peterson in 1968

continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 400540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A cedar, 27" dia., bears S.75°E., 120.8 lks., with healed blaze.
A hemlock, 17" dia., bears S.79°W., 105.5 ft. with healed blaze. (Rec. 106.3 ft.)
and BTs mkd. by Karlas Seidel, Coos Co. Surveyor, in 2000, filed in the Coos Co. Surveyor's Office, under Book 21 pg 147
A fir, 18" dia., bears N.13½°E., 52.4 ft. with a healed blaze.
A fir, 18" dia., bears N.43½°W., 40.3 ft. with a healed blaze.

Fd. OK by K DeGroot, 11/2011 - C.S. file 65/75-7

James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-18 A-C & revised map M166-43 A

Found - 3¼" brass cap on 2½" pipe stamped BLM 1968
BTs - 20" Fir with healed face & tag dated 08/00 N.16°E., 52.4' to nail in side center
35" 3 ft. tall stump with healed "X" N.39°15'E., 11.2'
17" hemlock with healed face & tag dated 6/68, S.79°W., 106.3'
19" W.Fir with healed face and Coos County tag dated 8/00, N.41°W., 63.4' to nail in side center

2