

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W. S. Chapman, Deputy Surveyor, under Contract #234, dated June 24, 1875 - (DCSO records Vol. 16 Page(s) 6631)

 Set post 4 ft. long, 5" dia., one ft. in ground for sec. cor., from which

- A Fir 90" dia., bears N.45°W., 6 lks.
- A Hemlock 8" dia., bears N.80°E., 29 lks.
- A Fir 70" dia., bears S.25°E., 48 lks.
- A Cedar 10" dia., bears S.60°W., 24 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C Putnam, crew - Aug. 17, 1959 - C.S. File 49/100-48

 Found - Orig. 90" now 90" Fir, N.45°W., 4.0 ft., shows good original bark scribing and more recent bark scribing.

Orig. 70" now 72" Fir, S.25°E., 31.7 ft., shows good bark scribing.

Orig. 8" now 14" Hemlock bears N.80°E., 19.1 ft., shows good scar.

Orig. 10" Cedar now 14", shows good scribing on old face.

Set Brass cap at cor. mkd: County Surveyors Office

C	T	29	S	R	9	W	D
0		S	4	S	3		0
0		S	9	S	10		U
S			1959				G

New BTs- 14" Hemlock bears N.87°W., 42.2 ft. scribed S4 T29S R9W D CS BT.

6" Hemlock bears S.53°E., 43.0 ft. scribed S10 T29S R9W D CS BT.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #606, surveyed May\June 1968 (DCSO records Vol. 35 Page(s) 14402)

 The Sec. cor., perpetuated and recorded by Byron in 1959, monumented with an iron post 36" long, 1½" dia., firmly set 24" in the ground with brass cap mkd. in 1959, from which the original bearing trees:

A sawed Hemlock stump 20" dia., bears N.85°E., 29 lks. no marks visible on opened and rotted blaze. (Rec. N.80°E.)

A sawed Fir stump 62" dia., bears S.25°E., 48 lks. dist., with fragmentary scribe marks visible on weathered bark blaze.

(Cont. Next Page)

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 400600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Cedar 18" dia., bears S.58°W., 26 lks. dist., with scribe marks 9S R9W visible on partially healed blaze. (Rec. S.60°W., 24 lks.)
A Fir root crown 80" dia., bears N.45°W., 6 lks. dist., no marks remaining.
and a bearing tree mkd. by Byron:
A Hemlock 21" dia., bears N.89°W., 64 lks. dist., with scribe marks T29S R9W S4 DCS BT visible on partially healed double blaze.
and new bearing trees:
A Hemlock 18" dia., bears N.18°E., 35 lks. dist., mkd. T29S R9W S3 BT.
A Hemlock 13" dia., bears S.37½°E., 75 lks. dist. mkd. T29S R9W S10 BT.

Found OK by W. Rogers, Mar. 2001 - M136-62 A & B

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2092, surveyed Sept. 2004/May 2005 - (DCSO records Vol. 56 Page(s) 22251-2)

The cor. of secs 3, 4, 9, & 10, monumented with an iron post, 1¾" dia., firmly set, projecting 16" above ground, with brass cap (properly) mkd.
from which the remains of the original bearing trees
A sawed, decayed fir stump, 62" dia., bears S.28½°E., 31.7 ft., with a healed blaze. (Record, S.25°E.)
A cedar, 30" dia., bears S.58°W., 17.2 ft., with a healed blaze.
A decayed fir root crown bears N.45°W., 4.0 ft., with no marks visible.
and remains of a BT mkd. by Byron, in 1959, and reported by Peterson
A roothole bears N.89°W., 42.2 ft., with fallen, decayed hemlock snag, 29" dia., lying alongside, with a healed blaze.
and BTs mkd. by Peterson
A hemlock, 25" dia., bears N.18°E., 23.1 ft., with a healed blaze.
A hemlock, 21" dia., bears S.37½°E., 49.5 ft., with a healed blaze.
and a new bearing tree
A hemlock, 17" dia., bears N.10½°W., 42.9 ft., mkd. T29S R9W S4 BT.

continued next page

2

PRIMARY CORNER DESCRIPTION Sec. Cor. for 3, 4, 9 and 10

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM retracement by Aaron M Graham, Cadastral Surveyor, under Group No 2300, surveyed Oct. 2007 - (DCSO records Vol. 56 Page(s) 22255 and BLM Plat 2010-3)

The cor. of secs. 3, 4, 9, & 10, monumented with an iron post, 1¾" dia., firmly set, projecting 16" above ground, with brass cap (properly) mkd.

from which the remains of the orig. BTs

A fir stump, fir stump, 62" dia., bears S.28½°E., 31.7 ft., with a healed blaze.

A cedar, 30" dia., bears S.58°W., 17.2 ft., with a healed blaze.

and the remains of a BT mkd by Byron in 1959 and reported by Peterson

A roothole bears N.89°W., 42.2 ft., alongside of which is a down hemlock 29" dia., with a healed blaze.

and BTs mkd. by Peterson

A hemlock, 25" dia., bears N.18°E., 23.1 ft., with a healed blaze.

A hemlock, 22" dia., bears S.37½°E., 49.5 ft., with a healed blaze.

and a BT by Skeesick in 2004-5

A hemlock, 17" dia., bears N.10½°W., 42.9 ft., mkd. T29S R9W S4 BT.

Latitude 43°04'07.76"N Longitude 123°45'41.78"W
(NAD 1983 (CORS))

The geodetic position shown heron was computed from the 2004-05 survey by A. Bert Skeesick, accepted Aug. 18, 2010

James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-18 A-C & revised map M166-43 A

Found - 2½" brass cap on 1" pipe stamped COOS COUNTY 1959
BTs - 31" Hemlock with healed face and BLM tag dated 5/68, N.18°E., 23.1'

24" Fir with healed face and BLM tag dated 05/68, S.37½°E., 49.5'

55" stump 6 ft. tall with tag dated 1998, S.25°E., 31.7'

31" Cedar with tag dated 1998, S.58°W., 17.2'

19.5" Hemlock with visible scribe & tag dated 5/03/05, N.10¼°W., 42.9' to nail in side center.