

PRIMARY CORNER DESCRIPTION C C for Secs. 15 & 16 only (North)

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO resurvey by William M. Porter, Deputy Surveyor, contract #768, dated March 8, 1907 - (DCSO records Vol. 16 Page(s) 6644-45)

At a point 75 lks. E. of cor. of secs. 9, 10, 15 and 16, Set a basalt stone 20x15x8 ins., 15" in the ground, at point of intersection, for closing cor. of secs. 15 and 16, marked CC on S. face and 4 notches on S. and 3 notches on E. edges, from which

- A Hemlock 8" dia., bears S.23°E., 60 lks. mkd. T29S R9W S15 BT.
- A Hemlock 24" dia., bears S.32°W., 8 lks. mkd. T29S R9W S16 BT.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #606, surveyed May\June 1968 (DCSO records Vol. 35 Page(s) 14400-01)

True point for the closing cor. of secs. 15 and 16.
Set an iron post 28" long, 2½" dia., 24" in the ground with brass cap marked:

T 29 S R 9 W
S 10

S 16 S 15
CC
1968

from which

- A Chinquapin 5" dia., bears S.70°E., 82 lks. dist. mkd. T29S R9W S15 CC BT.
- A Fir 12" dia., bears S.64°W., 120 lks. dist. mkd. T29S R9W S16 CC BT.

From this point, the cor. of secs. 9 and 10 only, bears S.89°39'W., 0.54 chs. dist.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2092, surveyed Sept. 2004 - May 2005 - (DCSO records Vol. 56 Page(s) 22244)

N.0°19'26"E., bet. secs. 15 and 16.
2750.20 ft: The original closing cor. of secs. 15 and 16, monumented with the original sandstone stone, 20x15x8" firmly set, with 4 grooves on S. and 3 grooves on E. faces.
At the corner point
Drive an iron rebar, 5/8" dia., 30" long, 30" in the ground and bury the original stone inverted alongside the rebar.
2750.20 ft: The closing cor. of secs. 15 and 16, monumented with an iron post, 2½" dia., firmly set, projecting 10" above ground, with brass cap mkd.

continued next page