

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6629)

Set ¼ sec. post, from which
A Fir 12" dia., bears S.44°E., 13 lks.
A Fir 12" dia., bears N.22°W., 16 lks.

GL0 resurvey by William M. Porter, Deputy Surveyor, Under Special Instructions dated June 5, 1907, Independent of, but in connection with his contract #768, dated March 8, 1907 - (DCSO records Vol. 16 Page(s) 6637)

Intersect at point for ¼ sec. cor. Post gone; witness trees standing and agree with notes furnished by the surveyor general. Basalt stone 12x10x6 ins., 8" in the ground mkd. ¼ on N. face.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Sept. 1959 - C.S. File 49/100-55

Found Stone at corner as recorded by Porter and both orig. BTs.
Orig. 12" now 20" Fir stump, N.22°W., 9.0 ft., shows good scar. I do not open.
Orig. 12" now 26" Fir S.44°E., 8.6 ft., shows good scribing "¼".
Set brass cap alongside corner stone, and mark ¼ S22 S27 T29S R9W County Surveyors Office 1959.
New BT - 16" R.Fir N.22°W., 41.4 ft. scribed ¼ S22 CS BT.

Douglas Co. Surveyors Office - John M. Powell, and crew - Dec. 7, 1965 - C.S. File 53/53-77

Found - Brass cap at cor. mkd. in 1959.
Orig. 26" Fir stump S.44°E., 8.6 ft.
20" Fir stump N.22°W., 9.0 ft.
16" R.Fir now 17", N.22°W., 41.4 ft., shows 2 good faces.
New BT - 17" Fir S.10°W., 33.5 ft. scribed ¼ S27 CS BT.
Corner is on top of ridge just before descending, going West. Possible to walk to corner on old road from NW. section cor. of sec. 27.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias	Description
Alias	Description
Alias	Description
Alias	Description

Douglas Co. Surveyors Office - Stephen Flause; John Pike, crew - Oct. 15, 1996 - C.S. File 65/9-28

Found - A 2½" dia. 1959 DCS0 brass cap on a 1½" O.D. Galv. Iron pipe, firmly set and protruding approx. 18" out of the ground.

A buried stone on the North edge of the brass cap monument with the marks "1/" visible, protrudes approx. 4" above ground. Record from 1907 retracement survey calls for a 12" x 10" x 6" basalt stone; the found stone is sandstone but the size is reasonable and the markings appear to be time worn.

Orig. BT, a Fir 12" dia., now a 28" dia., 3 ft. tall, rotted Fir stump with no original markings found, bears S.44°E., 9.3 ft. (Rec. S.44°E., 8.6 ft. a face measurement)

A Fir 12" dia., now a 24" dia., 3 ft. tall, rotted Fir stump with remains of a healed blaze, now opened to reveal partial illegible scribing, bears N.22°W., 9.3 ft. (Rec. per 1959, N.22°W., 9.0 ft.) O.B.T.

The BT marked in 1959, a 16" R.Fir, now a 24" dia., low cut Fir stump with possible remains of lower blaze edge, bears N.23 ¾°W., 44.4 ft. (Rec. per 1959, N.22°W., 41.4 ft.)

The BT marked in 1965, a 17" Fir, now 19" DBH D.Fir with a fully healed double blaze, bears S.10°W., 33.5 ft. (as per record)

New BTs- A 10" DBH D.Fir scribed "¼ S22 CS BT" on a double blaze, bears N.36°E., 13.1 ft.

A 17" DBH D.Fir scribed "¼ S27 CS BT" on a double blaze, bears S.49°E., 72.1 ft.

A 9" DBH Madrone scribed "¼ S22 CS BT" on a double blaze, bears N.25°W., 41.0 ft.

Monument lies approx. 25 ft. North of abandoned logging road running easterly-westerly. (Sketch in C.S. File)

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #2043, surveyed May/June 2003 - (DCS0 rec. Vol. 55 Page(s) 21351-2)

The ¼ sec. cor. of secs. 22 & 27, remonumented by the Douglas County Surveyor's Office in 1959, & perpetuated by the Douglas County Surveyor's Office in 1965 & 1996, monumented with an iron post, 1½" dia., firmly set, projecting 17" above ground, with the original stone alongside,

continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 440300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 22 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

showing 4x10x4" above ground and fragmentary chisel marks visible on N. face, with brass cap (properly) mkd. from which the remains of the original bearing trees

- A fir stump, 28" dia., bears S.44°E., 9.3 ft., with no marks visible. (Record, 8.6 ft.)
- A sawed fir stump, 24" dia., bears N.22°W., 9.3 ft., with no marks visible. (Record, 10.6 ft.)

and the remains of a BT mkd by DC Surveyor's Office in 1959

- A sawed fir stump, 20" dia., bears N.23¼°W., 44.5 ft., with no marks visible.

and a BT mkd. by the Douglas County Surveyor's Office in 1965

- A fir, 21" dia., bears S.9½°W., 33.2 ft., with a healed blaze.

and the bearing trees mkd by the DC Surveyor's Office in 1996

- A fir, 12" dia., bears N.36¼°E., 13.1 ft., with a healed double blaze.
- A fir, 17" dia., bears S.49°E., 72.0 ft., with a healed double blaze.
- A madrone, 9" dia., bears N.25°W., 40.7 ft., with scribe marks ¼ S22 BT visible on a partially healed blaze.