

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 10 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. S. Champman, Deputy Surveyor, under Contract #234, dated June 24, 1875 - (DCSO records Vol. 16 Page(s) 6630)

-----  
Set post 4 ft. long, 4" dia., one ft. in ground, for ¼ sec. cor., from which  
A Cedar 8" dia., bears S.82°W., 33 lks.  
A Hemlock 20" dia., bears N.20°W., 39 lks.

GLO resurvey by William M. Porter, Deputy Surveyor, Under Special Instructions dated June 5, 1907, Independent of, but in connection with his contract #768, dated March 8, 1907 - (DCSO records Vol. 16 Page(s) 6641)

-----  
Point for ¼ sec. cor., post destroyed. Witness trees standing and agree with notes furnished by the surveyor general. Set a Cedar post 3 ft. long, 4" sq., 24" in the ground marked ¼ S10 on N. face and 15 on S. faces in place of the old cor.

J. N. Gearhart - Wit: M.S. Hubbard; Jack Densler - June 1950 - C.S. File 40/253

-----  
I find both BTs to be dead snags.  
I mark a Hemlock 9" dia., ¼ S15 BT 1743, bearing S.4°00'W., 20.2 ft. distant.  
Measurements to axillary center of tree at top of root crown.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Sept. 1, 1959 - C.S. File 49/100-50

-----  
Found - 9" now 9" dead Hemlock S4°W., 20.2 ft., scribing visible, "¼ S15 BT". This is BT recorded by Gearhart in 1950.

I do not find original BTs. Corner checks call West to creek OK.

Set Brass cap at cor. mkd: County Surveyors Office  
T 29 S R 9 W  
South ¼ S10  
1959

Corner is under 30" Fir log.  
New BTs- 60" Cedar snag N.60°W., 55.5 ft. scribed S¼ S10 CS BT.  
16" Hemlock bears N.72°E., 58.9 ft. scribed ¼ S10 cS BT.

(Cont. Next Page)

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 440500

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 10 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Fd. and Used in BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #606, surveyed May/June 1968 (DCSO records Vol. 35 Page(s) 14398-99)

Wayne Rogers - For: The Timber Co. - March 2001 - M136-62 A&B  
-----  
Found - Monument & BTs per 1968 BLM survey.  
NW BT is now a snag.  
New BTs- A 12" dia. Fir bears N.55°E., 9.1 ft. mkd: ¼ S10 BT.  
A 6" dia. Fir bears N.6½°W., 30.5 ft. mkd: ¼ S10 BT.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2092, surveyed Sept. 2004 - May 2005 - (DCSO records Vol. 56 Page(s) 22246-7)  
-----  
The ¼ sec. cor. of sec. 10 only, on the S. bdy. of sec. 10, monumented with an iron post, 1¼" dia., firmly set, projecting 18" above ground, with brass cap (properly) mkd. from which the remains of a bearing tree mkd. by J.N. Gearhart, Coos County Surveyor, in 1950, and reported by Peterson as marked by Byron  
A decayed hemlock stump, size indeterminate, bears S.3½°W. 20.5 ft., with no marks visible. (Record, South)  
and BTs mkd. by Byron, in 1959, and reported by Peterson  
A hemlock, 22" dia., bears N.72¾°E., 59.4 ft., with a healed blaze and X mkd. in the bark. (Record, N.67°E., 58.7 ft.)  
A burned cedar snag, 60" dia., bears N.62°W., 54.1 ft., with a healed blaze and X mkd. in the bark. (Record, N.60°W.)  
and remains of BTs mkd. by Rogers, in 2001  
A fir, 12" dia., bears N.61¼°E., 8.8 ft., with a healed blaze.  
A fallen fir snag, 7" dia., bears N.7¾°W., 30.7 ft., with a healed blaze.

James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-18 A-C & revised map M166-43 B  
-----  
Found - 2½" brass cap stamped County Surveyor 1959  
BTs - 13" W.Fir with healed face with tag dated 01/01  
N.55°E., 9.1' to nail in side center