

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6622)

-----  
Set post corner of secs. 26, 27, 34 and 35, from which  
A Fir 18" dia., bears N.30°E., 4 lks.  
A Fir 12" dia., bears S.65°E., 5 lks.  
A Fir 24" dia., bears S.55°W., 16 lks.  
A Fir 24" dia., bears N.14°W., 42 lks.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14029)

-----  
(Found 1957 DCSO brass cap; 2 orig. BTs; 2 BTs by Byron)  
"Add marks BLM 1966 to brass cap"

Douglas Co. Surveyors Office - James W. Byron, Deputy - Oct. 13, 1959 - C.S. File 49/100-70

-----  
Found - Orig. 24" now 32" Fir stump, N.14°W., 27.7 ft., previously opened near base, shows good scribing "BT".  
Orig. 24" now 32" Fir stump S.55°W., 10.6 ft. I open and find good scribing "BT"  
No trace of SE. or SW. BT found.

Set Brass cap at cor. mkd: County Surveyors Office  
T 29 S R 9 W  
S 27 | S 26  
S 34 | S 35  
1959

New BTs- 10" W.Fir bears N.80°W., 45.9 ft. scribed S27 T29S R9W CS BT.  
7" W.Fir bears S.53°W., 23.8 ft. scribed S34 T29S R9W CS BT.  
14" Maple bears S.55°E., 29.5 ft. scribed S35 CS BT.  
10" Fir bears N.62½°E., 88½ ft. scribed S26 CS BT.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14028)

-----  
(Found DCSO 1959 brass cap; 2 orig. BTs.; and 4 BTs by Byron)  
"Add marks BLM 1966 to brass cap"

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Wayne L. Rogers Cadastral Surveyor and Garry L. Moore, Surveying Technician, under Group #1516, Surveyed Dec. 1989/March 1990 - (DCSO records Vol. 50 Pages 18976-77)

-----  
The Sec. Cor., monumented with an iron post 1¼" dia., firmly set, projecting 14" above ground with brass cap mkd. in 1959, from which the remains of original bearing trees:

A Fir stump 32" dia., bears S.45°W., 18 lks. dist., no marks visible.

A Fir stump 32" dia., bears N.14°W., 42 lks. dist., with scribe mark T visible on opened blaze.

and the remains of bearing trees mkd. by Byron in 1959:

A W.Fir 23" dia., bears N.61¼°E., 134 lks. dist., with double healed blaze.

A Maple 18" dia., bears S.57°E., 44¼ lks. dist., with double healed blaze.

A W.Fir snag 14" dia., bears S.57°W., 36 lks. dist., with double healed blaze.

A root hole, bears N.82°W., 69½ lks. dist.

and new bearing trees:

A Fir 12" dia., bears S.2°W., 72 lks. mkd. T29S R9W S34 BT

A Fir 16" dia., bears N.80°W., 53 lks. dist., mkd. T29S R9W S27 BT.

Fd. OK, March 1996 by K. Hoffine - M 123-59

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #2043, surveyed May/June 2003 - (DCSO rec. Vol. 55 Page(s) 21342-3)

-----  
The cor. of secs. 26, 27, 34, & 35, monumented with an iron post, 1¼" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd.

from which the remains of the original bearing trees

A fir stump, size indeterminate, bears S.45°W., 11.9 ft., with no marks visible.

A fir stump, 36" dia., bears N.14°W., 27.7 ft., with scribe mark T visible on an opened blaze.

and remains of BTs mkd. by the Douglas County Surveyor's Office, reported by Rogers and Moore

A fir, 25" dia., bears N.62½°E., 88.4 ft., with a healed double blaze. (Record, N. 61¼° E.)

A maple, 18" dia., bears S.57°E., 29.2 ft., with no marks visible.

A fir snag, 14" dia., bears S.51¼°W., 23.8 ft., with a healed double blaze. (Record, S.57°W.)

continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 500200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 26, 27, 34 and 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the bearing trees mkd. by Rogers and Moore  
A fir, 16" dia., bears S.0¾°W., 46.6 ft., with a healed blaze. (Record, S.2°W., 47.5 ft.)  
A fir, 20" dia., bears N.80°W., 35.0 ft., with a healed blaze.  
and a new bearing tree  
A fir, 17" dia., bears S.52¼°E., 37.6 ft., mkd. T29S R9W S35 BT.  
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description  
Corner is located 0.5 ft. S. of the cor. of barbed wire fences extending N., E., and W.