

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6623)

-----  
Set ¼ sec. post, from which  
    A Fir 12" dia., bears N.60°W., 25 lks.  
    A Cedar 30" dia., bears S.60°E., 29 lks.

J.W. Cole, Deputy Co. Surveyor - Wit: P.D. Wolford; G.A. MacHenry - Aug/Sept. 1920 - Vol. 3 pages 70-71; Field Book 48 Page 10+; C.S. File 6/17

-----  
Set 1" x 30" Iron pipe from which  
    A Cedar 10" dia., bears N.62°E., 14.5 ft.  
    A Fir 20" dia., bears N.61°15'W., 16 ft.  
Old stake standing but badly decayed. Cedar BT had been cut but stump remains.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Oct. 16, 1959 - C.S. File 49/100-68B

-----  
Found - Cole's 10" now 14" dead Cedar, N.62°E., 14.6 ft., shows good scribing "B".  
    Cole's NW. BT, down and mostly burned.  
    Also find 1" Iron pipe at corner.  
New BTs- 8" W.Fir bears S.5°E., 48.3 ft scribed ¼ S26 CS BT.  
    72" R.Fir bears S.78°W. 160.0 ft scribed ¼ S27 CS BT

Douglas Co. Surveyors Office - James W. Byron, Deputy - Mike Darby; Wm. Stoffel, crew - June 20, 1963 - C.S. 49/100-83

-----  
Found - 1" I.P. at corner.  
    8" now 9" W.Fir S.5°E., 48.3 ft., shows scribing.  
    SW. bearing tree, now down.  
New BT - 9" W.Fir bears S.6½°W., 68.0 ft. scribed ¼ S27 CS BT  
Corner is 25 ft. East of small stream.

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - D.L. Stewart, crew - Aug. 11, 1981 - C.S. File 61/27-29

-----  
Found - Orig. ¼ sec. post, not found.  
    Found ¾" x 30" I.P. (Rec. 1" x 30")  
    31" dia. Cedar stump (Rec. 30") bears S.60°E., 19.1 ft., no blaze or scribing found.  
    Dead windfall (orig. 10" Cedar) bears N.62°E., 14.5 ft. with scribed BT visible.

(Cont. Next Page)

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 500240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

20" W.Fir, (orig. 8") with well healed blaze bears S.5°E., 48.3 ft.  
22" W.Fir (Orig. 9") with well healed blaze bears S.6½°W., 68.0 ft.  
Set brass cap on a 1" x 30" I.P., stamped "Douglas County Surveyor T29S R9W 1/4 S27|S26 1981". Reset the found 3/4" I.P. alongside.  
New BTs- 10" W.Fir blazed and scribed "¼ S27 CS BT", bears N.39½°W., 62.7 ft.  
14" W.Fir blazed and scribed "¼ S27 CS BT" bears N.75°E., 49.5 ft.  
Monument is 3½ ft. East of a N-S fence.

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #2043, surveyed May/June 2003 - (DCSO rec. Vol. 55 Page(s) 21344-5)

-----  
The ¼ sec. cor. of secs. 26 & 27, perpetuated by the Do. Co. Surveyor's Office in 1920, 1959, & 1963, & remonumented by the Douglas County Surveyor's Office in 1981; monumented with an iron post, 1¼" dia., firmly set, projecting 7" above ground, (alongside of which is an iron pipe, 1" dia., firmly set projecting 6" from the ground) with brass cap (properly) mkd.  
from which the remains of the original bearing trees  
A burnt cedar stump, 31" dia., bears S.56¾°E., 20.4 ft., with no marks visible. (Record, S.60°E., 19.1 ft.)  
and the remains of a bearing tree mkd. by the Douglas County Surveyor's Office in 1959  
A fir stump, 35" dia., bears S.6¼°E., 48.2 ft., with no marks visible.  
and a BT mkd by the Douglas Co Surveyor's Office in 1963  
A fir, 31" dia., bears S.5¾°W., 67.7 ft., with a healed double blaze.  
and the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1981  
A fir stump, 21" dia., bears N.74¼°E., 49.1 ft., with no marks visible.  
A fir, 23" dia. bears N.40½°W., 62.3 ft. w/healed blaze.  
and a new bearing tree  
A fir, 12" dia., bears N.79½°E., 35.6 ft., mkd. ¼ S26 BT  
Each new bearing tree has a 2½"x¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description.  
Corner is located 4.2 ft E of woven wire fence extending N & S