

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6623)

Set post cor. secs. 22, 23, 26 and 27, from which
A Fir 12" dia., bears N.50°E., 27 lks.
A Fir 24" dia., bears S.54°E., 25 lks.
A Fir 12" dia., bears N.50°W., 36 lks.
A Fir 10" dia., bears S.62°W., 18 lks.

GL0 resurvey by William M. Porter, Deputy Surveyor, Under Special Instructions dated June 5, 1907, Independent of, but in connection with his contract #768, dated March 8, 1907 - (DCSO records Vol. 16 Page(s) 6637)

The sec. cor. post and one witness tree gone. Stump of tree and other witness trees agree with notes furnished by the Surveyor General.
Set a new post, a Yew 3 ft. long, 4" sq., 24" in the ground, mkd. T29S S23 on NE.; R9W S26 on SE.; S27 on SW.; and S22 on NW. faces, with 2 notches on S. and 2 notches on E. faces. The old witness trees as per notes furnished.
New BT - A Fir 10" dia., bears S.50°E., 52 lks. dist. mkd. T29S R9W S BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Sept. 1959 - C.S. File 49/100-54

Found - 12" now 30" W.Fir N.50°E., 17.8 ft., shows good scars. I do not open.
Orig. 10" now 20" Fir, S.50°E, 34.3 ft, previously opened, shows good scribing.
Orig. 12" now down 24" Fir, N.50°W., 23.8 ft., shows scribing on old face.
No trace of SW. BT found.

Set Brass cap at cor. mkd: County Surveyors Office

T 29 S R 9 W
S 22 | S 23
S 27 | S 26
1959

New BTs- 12" W.Fir bears S.67°E., 33.8 ft. scribed S23 T29S R9W CS BT.
12" Hemlock bears N.32°W., 32.2 ft. scribed S22 T29S R9W CS BT.
26" R.Fir bears S.31½°W., 28.0 ft. scribed S27 T29S R9W CS BT.

(Cont. Next Page)

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 500300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 22, 23, 26 and 27

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14019-20)

(Found 1959 DCSO brass cap; 2 Hathorn BTs; 1 Porter BT; and 3 Byron BTs.)
"Add marks BLM 1966 to brass cap"
Corner is located 8 lks. N. of a fence corner, fence lines extending S. and E.

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #2043, surveyed May/June 2003 - (DCSO rec. Vol. 55 Page(s) 21346)

The cor. of secs. 22, 23, 26, & 27, monumented with an iron post, 1¼" dia., firmly set, projecting 12 ins. above ground, with brass cap (properly) mkd. from which the remains of bearing trees mkd. by the Douglas County Surveyor's Office in 1959, reported by Jelley
A sawed fir stump, 31" dia., bears S.31½°W., 27.7 ft., with no marks visible.
A hemlock snag, 17" dia., bears N.32°W., 32.0 ft., with a healed blaze.
and the remains of bearing trees mkd. by person(s) unknown
A sawed fir stump with tin cap, 38" dia., bears N.76½°E., 9.9 ft., with no marks visible.
A fir, 11" dia., bears N.88¾°E., 21.0 ft., with scribe marks S23 BT visible on a partially healed blaze.
A fir, 11" dia., bears N.27°W., 43.5 ft., with scribe marks S22 BT visible on a partially healed blaze.
A cedar, 20" dia., bears N.3¾°W., 26.3 ft., with scribe marks S23 BT visible on a partially healed blaze.

The geographic position (NAD 1983 (CORS)), as determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of less than 0.02 feet, 95% confidence level, utilizing dual frequency, carrier phase GPS receivers, and National Spatial Reference System Continuously Operating Reference Stations (CORS) "CAPE BLANCO CORS ARP" and "DODSON BUTTE CORS ARP", is as follows:
The corner of sections 22, 23, 26 and 27:
Latitude: 43° 01' 31.70" N.
Longitude: 123° 44' 30.29" W.