

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6625)

Set ¼ sec. post, from which
A Laurel 6" dia., bears S.45°W., 30 lks.
A Laurel 5" dia., bears S.50°E., 10 lks.

GLO resurvey by William M. Porter, Deputy Surveyor, Under Special Instructions dated June 5, 1907, Independent of, but in connection with his contract #768, dated March 8, 1907 - (DCSO records Vol. 16 Page(s) 6639-40)

Point for ¼ sec. cor., post and witness trees gone. Stumps of witness trees standing and agree with notes furnished by the Surveyor General. Set a Cedar post 3 ft. long, 4" sq., 24" in the ground for sec. ¼ cor. mkd. ¼ S15 on the W. and 14 on the E. faces, from which
A Fir 10" dia., bears S.51°E., 54 lks. mkd. ¼ S14 BT.
A Fir 12' dia., bears N.62°W., 68 lks. mkd. ¼ S15 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Sept. 1959 - C.S. File 49/100-57

Found - Orig. 12" now 18" Fir, N.62°E., 44.9 ft. I open and find good scribing "1 S".
Orig. 10" now 16" down Fir, S.51°E., 35.6 ft., shows old face badly burned, no scribing found.
Set ¾" Iron rod at corner, which is on top of N.45°W. spur and center of Jeep road.
New BT - 22" R.Fir bears S.3½°E., 30.6 ft. scribed ¼ S14 CS BT.

Douglas County Surveyors Office - Gary L. Langlitz, Deputy and crew - Jan. 17, 1974 - C.S. File 56/43-4

Found - ¾" I.R. buried and bent in center of abandoned skid trail on top of spur ridge.
Record 22" D.Fir, now 26", bears S.3½°E., 30.6 ft. blazes plainly visible and partly grown over. (Rec. S.3½°E., 30.6 ft.)
Orig. 12" now 21" D.Fir, bears N.62°W., 44.9 ft. was opened previously and now healing over. (Rec. N.62°W., 44.9 ft.)
No trace of original SE. tree.
Removed I.R. and set brass cap, buried 4" below surface of ground, mkd. (Cont. Next Page)

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 500440

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>County Surveyors Office T 29 S R 9 W ¼ S 15 S 14 1974</p> <p>New BT - 14" D.Fir bears S.19°W., 46.4 ft. scribed ¼ S15 CS BT.</p>
<p>Greg Lang - 9/15/2004 - C.S. File 65/20-11 -----</p> <p>Found - DCS0 brass cap 26½" Fir bears N.63½°W., 44.2 ft.</p> <p>New - 8" Fir bears N.2½°E., 35.2' scribed "¼ S14 BT" 15" Fir bears S.56°E., 33.7' scribed "¼ S14 BT" 9" Fir bears S.80½°W., 48.2' scribed "¼ S15 BT"</p> <p>Note - We set spikes in the base of all bearing trees; bearings to the trees were measured with a total station & are based on the original GLO survey. Corner is located on top of ridge.</p>
<p>James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-18 A-C & revised map M166-43 B -----</p> <p>Found - 2" brass cap stamped County Surveyor 1974</p> <p>BTs - 11½" Fir with healed face and Roseburg Resources tag dated 9/04, N.2½°E., 35.2' to nail in side center 19.5" Fir with Roseburg Resource tag dated 9/04, S.56°E., 33.7' to nail in side center. 30" 22 ft. tall snag with healed face and BLM tag dated 9/59, S.3½°E., 30.6' 11.5" Fir with healed face and Roseburg Resources tag dated 9/04, S.80½°W., 48.2' to nail inside center. 28" Fir with healed face & Roseburg Resources tag dated 9/04, N.63½°W. 44.2' to nail in side center</p>
<p>2</p>