

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6625)

Set post cor. secs. 10, 11, 14 and 15, from which
A Fir 30" dia., bears S.60°W., 176 lks.
A Fir 10" dia., bears N.48°W., 88 lks.
A Fir 15" dia., bears S.30°E., 30 lks.
A Fir 20" dia., bears N.50°E., 6 lks.

Used and tied in GL0 survey by W. S. Champman, Deputy Surveyor, under Contract #234, dated June 24, 1875 - (DCSO records Vol. 16 Page(s) 6630)

GL0 resurvey by William M. Porter, Deputy Surveyor, Under Special Instructions dated June 5, 1907, Independent of, but in connection with his contract #768, dated March 8, 1907 - (DCSO records Vol. 16 Page(s) 6640)

At point for sec. cor., three witness trees and cor. gone. Stumps of witness trees standing and agree with notes furnished by the Surveyor general. Set a Fir post 3 ft. long, 4" sq., 24" in the ground for cor. mkd. T29S S11 on NE.; R9W S14 on SE.; S15 on SW.; and S10 on NW. faces with 4 notches on S. and 2 notches on E. edges, from which
A Fir 30" dia., bears N.5°E., 54 lks. dist. mkd. T29S R9W S11 BT.
A Fir 15" dia., bears S.45°E., 34 lks. dist. mkd. T29S R9W S14 BT.
A Laurel 10" dia., bears N.8°W., 13 lks., mkd. T29S R9W S10 BT.
A Fir 40" dia., old BT, bears S.60°W., 176 lks. mkd. T29S R9W S15 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Sept. 1959 - C.S. File 49/100-60

Found - Orig. 30" now 36" Fir N.5°E., 35.6 ft., I open and find good scribing.
Orig. 15" now 30" Fir S.45°E., 22.4 ft., shows good scar, I do not open.
Orig. 40" now large and rotted Fir stump, S.60°W., 116.2 ft., no scribing found.
No trace of original NW. BT found.

(Cont. Next Page)

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>Set Brass cap at cor. mkd: County Surveyors Office T 29 S R 9 W S 10 S 11 S 15 S 14 1959</p> <p>New BTs- 13" R.Fir bears N.52°E., 12.5 ft. scribed S11 T29S R9W CS BT. 7" R.Fir bears N.55°W., 14.5 ft. scribed S10 CS BT. 10" R.Fir bears S.29°W., 3.6 ft. scribed S15 T29S R9W CS BT.</p>
<p>BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14023)</p> <p>-----</p> <p>(Found 1959 DCSO brass cap; 1 orig. BT.; 2 BTs by Porter; 3 BTs by Byron) "Add marks BLM 1966 to brass cap"</p>
<p>Greg Lang - 9/15/2004 - C.S. File 65/20-9</p> <p>-----</p> <p>Found - DCSO brass cap 44" Fir bears N.8°E., 33.8' (not opened) 22½" Fir bears N.50°E., 11.8' 35½" Fir bears S.44½°E 21.9' (opened) 15" Fir bears S.36½°W., 3.5' 10½" Fir bears N.55°W., 14.8'</p> <p>Note - We set spikes in the base of all bearing trees; bearings to the trees were measured with a total station & are based on the original GLO survey. Corner lies on an easterly slope approx. 275' northwesterly of a landing.</p>
<p>BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor & Robert H. Browning, Survey Tech under Group #2158, surveyed April/May 2007 - (DCSO records Vol. 55 Page 21496)</p> <p>-----</p> <p>The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 1¼" dia., firmly set, projecting 20", above the ground, with brass cap (properly) mkd. from which bearing trees mkd. by Porter A fir, 48" dia., bears N.5°E., 34.3 ft., with healed blaze A fir, 37" dia., bears S.45°E., 22.4 ft. with healed blaze and BTs mkd. by Byron, in 1959, reported by Skeesick A fir, 24" dia., bears N. 52° E., 12.5 ft., with a healed double blaze. A fir, 16" dia., bears S. 29° W., 3.6 ft., with a healed double blaze.</p> <p>continued next page</p>

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 500500

PRIMARY CORNER DESCRIPTION Sec. Cor. for 10, 11, 14 and 15

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 12" dia., bears N.55°W., 14.5 ft., with a healed double blaze.
(NAD 1983 (CORS 96))
Latitude: 43°03'16.15" N.
Longitude: 123°44'30.04" W.

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2092, surveyed Sept. 2004 - May 2005 - (DCSO records Vol. 56 Page(s) 22245-6)

The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 1¼" dia., firmly set, projecting 20 ins. above ground, with brass cap (properly) mkd. from which bearing trees mkd. by Porter, reported by Jelley
A fir, 48" dia., bears N.5°E., 34.3 ft., with a healed blaze.
A fir, 36" dia., bears S.45°E., 22.4 ft., with fragmentary scribe marks visible on an opened blaze.
and BTs mkd. by Byron, in 1959, and reported by Jelley
A fir, 22" dia., bears N.52°E., 12.5 ft., with a healed double blaze.
A fir, 16" dia., bears S.29°W., 3.6 ft., with a healed double blaze.
A fir, 12" dia., bears N.55°W., 14.5 ft., with a healed double blaze.

James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-18 A-C & revised map M166-43 B

Found - 2½" brass cap stamped County Surveyor 1959 stamped BLM 1966
BTs - 23½" Fir with healed face and Roseburg Resources tag dated 09/04, N.50°E. 11.8' to nail in side center
37" Fir with healed face and Roseburg Resources tag dated 9/04, S.44½°E., 21.15' to nail in side center
16" Fir with healed face and Roseburg Resources tag dated 09/04, S.36½°W. 3.5' to nail in side center
12" Fir with healed face and Roseburg Resources tag dated 09-04, N.55°W., 14.8' side center
47" Fir with healed face and Roseburg Resources tag dated 09-04, N.8°E., 33.8' to nail in side center