

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6626)

Set post cor. secs. 2, 3, 10 and 11, from which
A Fir 15" dia., bears S.65°E., 29 lks.
A Fir 18" dia., bears N.45°E., 59 lks.
A Fir 36" dia., bears S.85°W., 36 lks.
A Fir 15" dia., bears N.55°W., 75 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Oct. 1959 - C.S. File 49/100-61

Found - Fir tree, 28" dia., S.58°E. (instead of S.65°E.)
19.1 ft. Bark scribing, old, visible "T29S R9 S1". Scar below suggests "BT" possibly in wood. This tree has been rescribe in bark more recently "T29S R9W S11 BT", looks 10 to 20 years old.
Fir tree, now 22" N.45°E., 38.9 ft., showing bark scribing on upper blaze. Has been knocked off by falling rock but portions of bark scribing remain "BT" plainly visible. Also shows lower scar. A rock, 8 ft. x 5 ft. x 3 ft. is lodged against West side of tree. (Rescribed this tree)
Remains of NW. and SW. BTs, both down, uprooted, which fit notes for bearing and distance as well as can be determined.

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 9 W
S 3 | S 2
S 10 | S 11
1959

Blaze and scribe 2 new BTs:
6" Hemlock N.45°W., 5.7 ft. "S3 CS BT"
8" Hemlock S.1°W., 22.0 ft. "S10 CS BT"

Fd. and Used in BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14024-24)

"Add marks BLM 1966 to brass cap"

Found OK by W. Rogers, Mar. 2001 - M136-62 A & B

continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2, 3, 10 and 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor, under Group No. 2092, surveyed Sept. 2004 - May 2005 - (DCSO records Vol. 56 Page(s) 22248)

The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 1¼" dia., firmly set, projecting 18" above ground, with brass cap (properly) mkd.

from which the remaining original bearing trees

A fir, 29" dia. bears N.45°E. 38.9 ft. with a healed blaze

A fir, 34" dia. bears S.60°E. 19.1 ft. with a healed blaze and BTs mkd. by Byron, in 1959, and reported by Jelley

A hemlock, 17" dia., bears S.1°W., 22.4 ft., with a healed blaze.

A hemlock, 16" dia., bears N.50°W., 5.6 ft., with a healed blaze.

The geographic positions (NAD 1983 (CORS)) of the following corners were determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of 0.050 meters or better, 95% confidence level, relative to the National Spatial Reference System stations noted above. ("CAPE BLANCO CORS ARP" and "DODSON BUTTE CORS ARP")

Latitude: 43°04'08.54"N. Longitude: 123°44'29.45"W.