

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T28-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

**ON THE COUNTY LINE - CHECK WITH COOS COUNTY
FOR POSSIBLY MORE INFORMATION**

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6615-16)

Set post cor. secs. 2, 3, 34 and 35, from which
A Fir 15" dia., bears S.10°E., 15 lks.
A Fir 15" dia., bears S.58°W., 32 lks.
A Fir 36" dia., bears N.38°E., 33 lks.
A Chinquapin 12" bears N.82°W., 27 lks.

BLM Resurvey by William W. Glenn, Cadastral Surveyor, under Group #'s 350 and 420, surveyed April/June 1959 - (DCSO records Vol. 30 Page(s) 12849)

The Sec. Cor., determined at record bearing and distance to the face, from the remains of the original bearing trees:

A Fir 40" dia., bears N.38°E., 35½ lks. dist. bark scribed T28S R9W S35 BT. (Rec. dist. 33 lks.)
A Fir snag 21" dia., bears S.58°W., 33½ lks. dist., bark scribed T29S R9W S3 BT. (Rec. dist., 32 lks.)

At the corner point

Set an iron post, 28" long, 2½" dia., 24" in the ground, and in a mound of stone, 2½ ft. base, to top, with brass cap mkd:

T 28 S R 9 W

S 34 | S 35

S 3 | S 2

T 29 S

1959

from which

A Fir 13" dia. bears S.3¼°E., 116 lks. mkd. T29S R9W S2 BT

A Hemlock 30" dia., bears S.71°W., 101 lks. dist., mkd. T29S R9W S3 BT.

A Hemlock 10" dia., bears N.70½°W., 85½ lks. dist., mkd. T28S R9W S34 BT.

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1000, surveyed Nov. 2001 - (DCSO rec. Vol. 53 Pages 20724-5)

The cor. of secs. 2, 3, 34, & 35, was rehabilitated but not recorded by L. LaFlamme for Georgia Pacific in 1986, monumented with an iron post, 2½" diam., firmly set, projecting 6" above ground, in a collar of stone, with brass cap (properly) mkd.

from which the remains of an original bearing tree continued next page

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A sawed fir stump, 34" diam., bears N.38°E., 23.4 ft., with no scribe marks visible. (Bark scribed in 1855, all of the bark is gone.)
and remains of a bearing tree mkd. by LaFlamme
A sawed cedar stump, 35" diam., bears S.86°W., 15.9 ft., with scribe marks S34 BT 378 visible on a partially healed blaze.
and new bearing trees
A hemlock, 10" diam., bears N.1½°E., 25.4 ft., mkd. T28S R9W S35 BT.
A hemlock, 14" diam., bears S.73½°W., 107.0 ft., mkd. T29S R9W S3 BT.
A hemlock, 8" diam., bears N.27°W., 42.8 ft., mkd. T28S R9W S34 BT.
Each new bearing tree has a 2½ x ¼" magnetic nail (MAG-NAIL) driven at the base on the right side-center.
There is no remaining evidence of bearing trees mkd. by Glenn due to logging activity.
Corner is located 15 ft. N of a dirt road at a yarder landing

Coos County Surveyors Office - Michael Dado, Surveyor - Crew: Matthew Martin & Bill Hales - 2/25/2015 - C.S. File 65/87-52

Found - 1959 3¼" brass cap on a 2½" iron pipe, 0.4' tall, in good condition and solid in the ground. Note: monument leans to the NW.
1875: 34" D.fir tall stump, 7.5' tall, N.40°E., 23.10' to left side center. We find a healed scar on the face with nails and bits of an old tag in place. **We chop** a new "X" in the face and paint the "X" and "BT" in blue and attach a new yellow Coos Co. tag. Note: There are logging foot holes cut into the face and right side of this stump. This stump may possibly be an orig Hathorn 1855 BT. Good Condition
1986: 30" W. Cedar tall stump, 6' tall, N.85°W., 16.0' to left side center. We find visible scribes in an open blaze (S34-BT 378) **We chop** a new high "X" and paint the open face, the "X" and "BT" on the stump in blue. Stump was fd by Skeesick 2001 (per BLM record)
2001: 18" Hemlock, S.75°W., 104.71' (S.73°30'W., 107.0' rec.) to right side center. We find a mostly healed blaze. **We paint** the face and a band around the tree in blue and add a new yellow Coos Co. tag. Good condition

continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 500700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 2 & 3; 34 & 35, T28-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

2001: 8" Hemlock stump, N.25°W., 42.66' to heart center. We find visible scribes. We paint the top of the stump in blue. Good condition.

New BT - 6" hemlock, N.30°W., 39.13' to a nail at right side center. We bark scribe "T28S R9W S34 BT" low and chop an "X" high. We paint the scribes and "X" in blue and attach a yellow Coos Co. tag.

dec 17°