

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 540140

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. for Sec. 35

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Wayne L. Rogers Cadastral Surveyor and Garry L. Moore, Surveying Technician, under Group #1516, Surveyed Dec. 1989/March 1990 - (DCSO records Vol. 50 Page(s) 18980)

Point for the center ¼ sec. cor. of sec. 35, at intersection with the E. and W. center line.

Set a stainless steel post 28" long, 2½" dia., 24" in the ground with brass cap mkd. T 29 S R 9 W

C¼ S 35
1990

from which

A Fir 15" dia., bears N.8½°E., 375 lks. dist. mkd. C¼ S35 BT.

A Fir 6" dia., bears S.15 ¾°E., 131 lks. dist. mkd. C¼ S35 BT.

Deposit white "DEEP-1" magnetic marker at base of stainless steel post.

From this point, United States Coast and Geodetic Survey triangulation station "CAMAS 2 1942" bears S.86°52'08"W., 189.076 chs. dist., monumented with a brass tablet 3½" dia., set flush in a concrete post 12 x 12 ins., firmly set, projecting 12" above ground in center of the base of lookout tower, with brass cap mkd. USC & GS CAMAS 1942.

Fd. OK, June 1994 by B. Shaner - M 119-29