

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 540200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 26 and 35

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

and a bearing tree marked by Byron:
An Oak 13" dia., bears N.63°E., 27 lks. with healed double blaze.
At the corner point
Set an iron post, 28" long, 2½" dia., the top 6" below the surface of a graveled driveway 15" wide, bears N. and S., with brass cap mkd:
T 29 S R 9 W
¼ S 26
S 35
1966
from which new bearing tree
A Fir 8" dia., bears S.41 3/4°W., 441 lks., mkd. ¼ S35 BT.

Fd. and Used in BLM resurvey by Wayne L. Rogers Cadastral Surveyor and Garry L. Moore, Surveying Technician, under Group #1516, Surveyed Dec. 1989/March 1990 - (DCSO records Vol. 50 Page(s) 18978)

Douglas Co. Surveyors Office - Stephen J. Flause - Kody Inda - 9/8/2008 - C.S. File 67/25-67

Found - 1966 BLM 3¼" dia., brass cap (properly mkd) on a 2½" O.D. IP, set 10" below surface of gravel driveway entrance. This monument has a 1/2" dia., iron rod set with its top 2" below surface on the north & south edge.
No OBTs found. No 1920 DCSO BTs found.
One 1951 Crowder BT fd., an 18" now 32" W.Oak, fully healed single blaze, bears N.62½°W., 123.0 ft. (record N.59½°W., 123.0 ft.)
No 1957 DCSO BTs found.
Two 1966 BLM BTs found:
A 13" now 17" W.Oak (we look for scribing, find none, this tree probably not 1957 Byron BT) bears N.63°E., 17.8 ft. (as per BLM record)
An 8" Fir now 26" dia., 4 ft. tall stump with fully healed single blaze, bears S.41¾°W., 291.1 (as per record)
1" dia., bolt 8" below ground bears S.4°E., 1.75 ft.
New - 17" BLM W.Oak, now scribed "¼ S26 CS BT" on double blaze bears N.63°E., 17.8 ft. (as per record)
Note - Monument is at double driveway entrance near south edge of Denn Road.

FD. BC by D. Beedle, 10/2008 - 2008-0089