

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 540340

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 23

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #2043, surveyed May/June 2003 - (DCSO rec. Vol. 55 Page(s) 21353)

Point for the center ¼ sec. cor. of sec. 23, at intersection with the E. and W. centerline.

Set a stainless steel post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd.

T29S R9W
C 1/4
S 23
2003

from which

A fir, 17" dia., bears S.25¾°W., 49.7 ft., mkd. C ¼ S23 BT

A fir, 16" dia., bears N.4¾°W., 38.7 ft., mkd. C ¼ S23 BT

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

Deposit a magnet, in a white plastic case, at the base of the stainless steel post.

Corner is located 11.0 ft. E. and 30.0 ft. N. of a gravel road, 16 ft. wide, bears N. 20° W. and S. 20° E.