

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page 6624)

-----  
Set ¼ sec. post, from which  
A W.Oak 18" dia., bears S.45°W., 153 lks.  
A W.Oak 12" dia., bears N.50°E., 50 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Sept. 1959 - C.S. File 49/100-52

-----  
Found - Orig. 18" now 40" W.Oak S.45°W., 105.0 ft. (Rec. 101.0 ft.), shows old face, now rotted, no scribing found.  
Orig. 12" now 14" Oak, down, I open and find good scribing "BT", N.50°E., 33.0 ft.  
Set Brass cap at cor. mkd: County Surveyors Office  
T 29 S R 9 W  
S 14  
S 23  
1959

New BTs- 12" R.Fir bears N.27°E., 47.9 ft. scribed ¼ S14 CS BT.  
17" R.Fir bears S.31°W., 4.8 ft. scribed ¼ S23 CS BT

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14022-23)

-----  
The ¼ sec. cor., perpetuated and recorded by Byron in 1959, monumented with an iron pipe 1" dia., firmly set, extending 14" above the ground, with brass cap mkd. in 1966 from which the original bearing trees  
A down Oak 15" dia., bears N.50°E., 50 lks. dist., with scribe marks ¼ visible on opened blaze.  
A burned Oak stump 24" dia., bears S.45°W., 160 lks .dist. (Rec. 153 lks.)  
and bearing trees mkd. by Byron  
A Fir 18" dia., bears N.27°E., 72½ lks. dist., with healed double blaze.  
A down Fir 14" dia., bears S.31°W., 7 lks. dist., with healed double blaze.  
and a new bearing tree  
A Fir 13" dia., bears S.8°W., 173 lks. dist., mkd. ¼ S23 BT.  
Add marks BLM 1966 to brass cap.  
Corner is located at edge of timber, bears N. and S.

continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Douglas Co. Surveyors Office - M. Lenora Ladig; Jim H. Cook, crew - July 28, 1976 - C.S. File 59/18-8

-----  
Found - 1959 DCSO brass cap properly mkd., laying on ground, pulled out by cat.  
18" now 22" Fir, N.27°E., 47.9 ft. Tree is alive with healed blaze.  
14" Fir S.8°W., 114.2 ft. with healed blaze.  
At true corner point, RESET the DCSO brass cap 2" above ground. Added "DCSO" 1976 to East side of cap.  
Corner lies in old cat road.

Gary Smithers - For: Moore Mill & Lumber Co. - July/Aug. 2000 - M 135-53

-----  
Found - 2½" brass cap on iron pipe marked per rec. M 95-75B. Set in Fence line.  
21" D.Fir N.27°E., 48.0 ft. to spike side center with healed face & BT tag.  
Did not look for 14" Fir snag at S.8°W., 114.3 ft. in reproduction stand.  
New BTs- 12" W.Fir, N.39°W., 16.9 ft. to spike side center scribed ¼ S14 BT with BT tag.  
20" W.Fir N.27°E., 30.5 ft. to spike side center scribed ¼ S14 BT with BT tag.  
8" D.Fir N.66°E., 13.7 ft. to spike side center scribed ¼ S14 BT with BT tag.

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #2043, surveyed May/June 2003 - (DCSO rec. Vol. 55 Page(s) 21349-50)

-----  
The ¼ sec. cor. of secs. 14 & 23, perpetuated by Gary T. Smither, in 2000, monumented with an iron post, 1¼" dia., firmly set, projecting 3" above ground, with brass cap (properly) mkd.  
from which the remains of an original bearing tree  
A decayed oak stump, size indeterminate, bears S.39½°W., 103.6 ft., with no marks visible. (Record, S.45°W., 105.6 ft.)  
and a bearing tree mkd. by the Douglas County Surveyor's Office, reported by Jelley  
A fir, 22" dia., bears N.27°E., 47.9 ft., with healed double blazes.  
and the remains of a bearing tree mkd. by Jelley  
A fallen, decayed fir, size indeterminate, bears S.8°W., 114.2 ft., with no marks visible. continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 540400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 14 and 23

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and the bearing trees mkd. by Smither  
A fir, 21" dia., bears N.25 $\frac{3}{4}$ °E., 30.3 ft., with scribe marks  $\frac{1}{4}$  S14 BT visible on a partially healed blaze.  
A fir, 8" dia., bears N.63°E., 13.6 ft., with scribe marks  $\frac{1}{4}$  S14 BT visible on a partially healed blaze.  
A fir, 13" dia., bears N.62 $\frac{3}{4}$ °W., 17.0 ft., with scribe marks  $\frac{1}{4}$  S14 BT visible on a partially healed blaze.  
and a new bearing tree  
A fir, 6" dia., bears S.16 $\frac{3}{4}$ °W., 11.6 ft., mkd.  $\frac{1}{4}$  S23 BT.  
Each new bearing tree has a 2 $\frac{1}{2}$ "x  $\frac{1}{4}$ " magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

The geographic position (NAD 1983 (CORS)), as determined by a direct tie to a temporary point for which a position had been determined, to an accuracy level of less than 0.02 feet, 95% confidence level, utilizing dual frequency, carrier phase GPS receivers, and National Spatial Reference System Continuously Operating Reference Stations (CORS) "CAPE BLANCO CORS ARP" and "DODSON BUTTE CORS ARP", is as follows:  
The  $\frac{1}{4}$  section corner of sections 14 and 23:

Latitude: 43° 02' 23.76" N.  
Longitude: 123° 43' 55.11" W.

Ronald L. Rice, Ward NW - Jason Collver - March 20, 2012 - C.S. File 65/76-35

-----  
Found - DCS0 2 $\frac{1}{2}$ " brass cap on iron pipe, dated 1959, 1966, 1976. Set in fence line.  
D.Fir, 22" dia., bears N.27°E., 47.9 ft., with healed double blazes.  
W.Fir snag, 22" dia., bears N.25 $\frac{3}{4}$ °E., 30.3 ft., with scribing visible  
D.Fir, 10" dia., bears N.63°E., 13.6 ft., with healed blaze.  
W. Fir stub, 13" dia. x 5 ft. tall, bears N.62 $\frac{3}{4}$ °W., 17.0 ft., with scribing visible.  
D.Fir, 6" dia., bears S.16 $\frac{3}{4}$ °W., 11.6 ft., down  
New - 14" W.Fir bears N.58°W 29.8 ft. blazed, scribed,  $\frac{1}{4}$  S14 BT  
Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.  
Compass Declination 16° East