

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 2; & S 35, T29-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7373)

-----  
Set ¼ sec. post, from which  
A Fir 30" dia., bears N.67°E., 16 lks. dist.  
A Laurel 6" dia., bears S.71°W., 32 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Oct. 20, 1959 - C.S. File 49/100-72

-----  
Found - Orig. 30" now 40" Fir, N.67°E., 10.6 ft., shows good bark scribing "¼S". Also shows good scar at base.

No trace of orig. SW. BT found.  
Set Brass cap at cor. mkd: County Surveyors Office  
¼  $\frac{S\ 35}{S\ 2}$  T29S R9W  
T30S R9W  
1959

New BTs- 8" W.Fir bears N.31°E., 16.9 ft. scribed ¼ S35 CSBT  
15" R.Fir bears S.15°W., 37.8 ft. scribed ¼ S2 CSBT.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14026-27)

-----  
The ¼ sec. cor., perpetuated by Byron in 1959, monumented with an iron pipe 1" dia. firmly set, extending 14" above the ground, with brass cap mkd. in 1959, from which the remaining original bearing tree:

A Fir 42" dia., bears N.67°E., 16 lks. dist., with scribe marks ¼ S visible on weathered bark blaze and with healed blaze at base.

and bearing trees mkd. by Byron:

A W.Fir 12" dia., bears N.31°E., 25½ lks. dist., with healed double blaze.

A Fir 17" dia., bears S.13°W., 57 lks. dist., with healed double blaze.

Add marks BLM 1966 to brass cap.

Fd. and Used in Sec. Subd. survey by BLM resurvey by Wayne L. Rogers Cadastral Surveyor and Garry L. Moore, Surveying Technician, under Group #1516, Surveyed Dec. 1989/March 1990 - (DCSO records Vol. 50 Page(s) 18979)

continued next page

TOWNSHIP 30 RANGE 09 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 2; & S 35, T29-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ron Quimby - Crew: N. Fromdahl & R. Olsen - 4/2015 - C.S.  
File 65/87-48

-----  
Found - DCS0 brass cap (properly mkd)  
25" W.Fir N.31°E., 16.8 ft. Good scar.  
43" D.Fir N.67°E., 10.6 ft. Visible "S" on bark  
scribe.  
21"x7' tall fir stump S.13°W., 37.6 ft. good scar.  
New BT - 16" Fir S.25°E., 16.6 ft. scribed ¼ S2 BT.  
Note - Hand held Lat & Long NAD 1983  
N 42°59.774  
W 123°43.927  
Corner is approx. 150' south of road at corner of  
partial cut unit.