

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; 1 & 2, T30-9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 17 Page(s) 7373)

Set post cor. secs. 1, 2, 35 and 36, from which
A Fir 50" dia., bears S.35°E., 46 lks. dist.
A Fir 36" dia., bears N.1°E., 32 lks. dist.
A Fir 15" dia., bears N.57°W., 9 lks. dist.
A Fir 30" dia., bears S.60°W., 91 lks. dist.

A. Boyer, Deputy Co. Surveyor - Wit: J.N. Nelson; J.W. Priest - Feb. 24, 1943 - Vol. 4 Page 96

Renewed from two stumps of original witness trees in secs. 35 and 36, which were found, both being at top of cut for highway. Set a 4" x 4" post for corner from which the following newly scribed trees bear
A 13" Maple N.5°W., 34.5 ft.
A 12" Fir S.42°W., 2.0 ft.
A 24" Fir N.72°W., 34.5 ft.
Measurements made on slopes.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; Clete Putnam, crew - Oct. 20, 1959 - C.S. File 49/100-73

Found - Boyer's BTs, now stumps, show scribing.
Set corner from 12" Fir stump N.42°W., 2.0 ft.
Set Brass cap at cor. mkd: County Surveyors Office

S35	S36	T29S	
S 2	S 1	T30S	R9W

1959

Brass cap set in concrete.
New BT - 23" Cedar bears S.66°E., 125.0 ft. scribed S1 T29S R9W CS BT.
Set PK on yellow line, S.66°E., 33.8 ft. from corner in centerline of State Hwy. #42

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14004-05)

The Sec. cor., perpetuated and recorded by Boyer in 1943, subsequently remonumented and recorded by Byron in 1959, monumented with an iron pipe 1" dia., firmly set in concrete, extending 20" above the ground with brass cap mkd. n 1959, from which the remaining original bearing trees:
(Cont. Next Page)

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

A sawed Fir stump 36" dia., bears N.1°E., 35 lks., with scribe marks BT visible on opened blaze. (Rec. 32 lks.)
A rotted Fir stump 14" dia., bears N.57°W., 9 lks. with scribe marks BT visible on opened blaze.
and bearing trees mkd. by Boyer:
A rotted Fir stump 10" dia., bears S.42°W., 3 lks. with scribe marks CS BT visible on opened blaze.
A Maple stump 18" dia., bears N.5°W., 52 lks., with scribe marks CS S36 T29S R9W BT visible on opened double blaze and a bearing tree mkd. by Byron:
A Cedar 24" dia., bears S.66°E., 189 lks., with scribe marks T30S R9W S1 CS BT visible on open double blaze and new bearing trees:
A Fir 4" dia., bears N.28°E., 101 lks. mkd. X BT.
A Fir 4" dia., bears S.75°W., 46 lks. mkd. X BT.
No bearing trees available to the NW. within limits.
Add marks BLM 1966 to brass cap.

Fd. OK, Jan. 12, 1974 by B. Shaner - M 49-51
Fd. OK, 1975 by OSHD - "N-8"

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor Under Group No. 2500, Surveyed May/June 2012 - DCSO records BLM Plat 2013-1, T29-9 and Vol. 58 Page(s) 22977

The cor. of secs. 1, 2, 35, & 36, on the S. bdy. of the Tp. monumented with an iron post, 1¼" dia., firmly set, projecting 14" above ground, with brass cap (properly) mkd. from which the remains of the original BTs
A sawed, decayed fir stump, size indeterminate, bears N.6¼°E. 23.1 ft. with no marks visible. (Rec. N.1°E.)
A roothole bears N.57°W., 5.9 ft., with decayed stump fragments lying alongside.
and remains of BTs mkd. by Boyer, in 1943
A decayed maple stump, size indeterminate, bears N.5°E., 34.3 ft., with no marks visible. (Record, N.5°W.)
A decayed fir stump, size indeterminate, bears S.42°W., 2.0 ft., with no marks visible.
and a BT mkd. by Byron, Deputy County Surveyor, in 1959
A cedar, 34" dia., bears S.66¾°E., 123.5 ft., with a healed blaze. (Record, S.66°E., 124.7 ft.)
and remaining BT mkd. by Jelley in 1966
A fir, 27" dia., bears S.65½°W., 30.4 ft., with a healed blaze. (Record, S.75°W.)
and a new bearing tree
A fir, 9" dia., bears N.39¼°E., 21.3 ft., mkd. T29S R9W S36 BT.
continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36; 1 & 2, T30-9

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Corner is located 24 ft. N. of an old graveled road, 16 ft. wide, bears N. 200 E. and S. 300 W., and 72 ft. N. of the Middle Fork Coquille River, 22 ft. wide, course S. 200 W.