

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol 16 Pgs 6616-17)

-----  
Set ¼ sec. post, from which  
A Fir 9" dia., bears S.75°W., 7 lks.  
A Fir 10" dia., bears S.72°E., 46 lks.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14005)

-----  
The ¼ sec. cor., determined at record bearing and distance from the remaining original bearing tree:  
A burned Fir snag 14" dia., bears S.72°E., 46 lks. dist., with old axe marks visible on burned blaze.

At the corner point  
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 29 S R 9 W  
¼  
S 35 | S 36  
1966

from which new bearing trees:  
A Madrone 5" dia., bears S.75°E., 28 lks. mkd. ¼ S36 BT.  
A Fir 10" dia., bears N.83°W., 109½ lks. mkd. ¼ S35 BT.  
From this point, an iron axle 1" dia., firmly set, extending 14" above the ground, bears S.37°W., 0.024 chs. dist.

Fd. OK, June 1984 by D. Stringer - M 97-4

Survey by Kris DeGroot, LS #1941 - For; Desrosiers, Serge - April 15, 1987 - C.S. File 63/35

-----  
Found - A 2½" Iron post, firmly set, projecting 6" above the ground with a US BLM brass cap mkd. in 1966.  
20" D.Fir bears N.83°W., 72.3 ft. with healed blaze.  
New BTs- 8" D.Fir bears S.66°W., 26.7 ft. scribed ¼ S35 BT.  
8" D.Fir bears N.36°E., 99.2 ft. scribed ¼ S35 BT.

Fd. and Used in BLM resurvey by Wayne L. Rogers Cadastral Surveyor and Garry L. Moore, Surveying Technician, under Group #1516, Surveyed Dec. 1989/March 1990 - (DCSO records Vol. 50 Page(s) 18973)

Fd. OK, Feb. 1997 by D. Bentz - M 126-39

continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 35 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM Dependent Resurvey by A Bert Skeesick, Cadastral Surveyor  
Under Group No. 2500, Surveyed May/June 2012 - DCSO records  
BLM Plat 2013-1, T29-9 and Vol. 58 Page(s) 22977

-----  
The ¼ sec. cor. of secs. 35 & 36, monumented with an iron  
post, 2½" dia., firmly set, projecting 4" above ground with  
brass cap (properly) mkd.

from which the remaining BT mkd. by Jelley in 1966

A fir, 28" dia., bears N.83°W.. 72.3 ft., with a healed  
blaze.

and BTs mkd. by DeGroot, in 1987

A fir, 24" dia., bears N.36°E., 99.0 ft., with a healed  
blaze.

A fir, 19" dia., bears S.66°W., 26.7 ft., with a healed  
blaze.

Latitude 43°00'13.00"N. Longitude 123°43'19.13"W.  
(NAD 1983 (CORS 96))

Fd. Brass cap by T Hostetter - July 2022 - 2022-0034