

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias 044040 Description SF Cor. Adam Day DLC #44
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6617)

Set post cor. secs. 25, 26, 35 and 36, from which
An Oak 18" dia., bears N.82°E., 1508 lks.
An Oak 20" dia., bears S.27°E., 271 lks.
An Oak 18" dia., bears S.24°W., 596 lks.
An Oak 15" dia., bears N.85°W., 1115 lks.
Adam Day's house bears N.23°W.

DLC Survey by J.A. Burnett, under Contract #75 dated Nov. 22, 1856 - (DCSO records, DLC Volume, Page 591

At the NW. corner sec. 36, from which
An Oak 18" dia., bears N.82°00'E., 1508 lks.
An Oak 15" dia., bears N.85°W., 1115 lks.

J. W. Cole, Deputy Co. Surveyor - Wit: P.D. Wolford; G.A. MacHenery - Aug/Sept. 1920 - Vol. 3 Pg. 70-71; Field Book 48 Page 10; C.S. File 6/17

Set 2" iron pipe beside old corner stake. Original BTs standing.

F.C. Frear - Hector survey - Wit: H. Crowder - July 10, 1951 - C.S. File 44/47-8

Found 3" Pipe as set by J.W. Cole for corner. Scribed:
24" Fir N.68°W., 18.1 ft.
14" Fir N.56°E., 28.2 ft.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14006)

The Sec. cor. perpetuated and recorded by Cole in 1920, monumented with an iron pipe 2" dia., firmly set, extending 3" above the ground from which the remaining original bearing trees:

A burned Oak stump 36" dia., bears S.27°E., 271 lks. dist., no marks remain.
A burned Oak stump 24" dia., bears S.23°W., 599 lks. dist., no marks remain. (Rec. S.24°W., 596 lks.)
and bearing trees mkd. by J.N. Gearhart, in 1950 (??)
A Fir 20" dia., bears N.56°E., 44 lks. dist., with healed double blaze.

(Cont. Next Page)

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25, 26, 35 and 36

Alias 044040 Description SE. Cor. Adam Day DLC #44
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A Fir 28" dia., bears N.68°W., 28½ lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 29 S R 9 W

S 26 | S 25

S 35 | S 36

1966

from which a new bearing tree

A Fir 9" dia., bears S.80½°E., 300 lks. dist. mkd. T29S R9W S36 BT.

No bearing tree available to SW. within limits.

Reset iron pipe alongside the iron post.

Fd. OK June 1984 by D. Stringer - M 97-4 EXCEPT the 28" Fir, N.68°W., is now a 4 ft. stump

BLM resurvey by Wayne L. Rogers Cadastral Surveyor and Garry L. Moore, Surveying Technician, under Group #1516, Surveyed Dec. 1989/March 1990 - (DCSO records Vol. 50 Page(s) 18974-75)

The Sec. Cor., monumented with an iron post, 2½" dia., firmly set, projecting 5" above ground, with brass cap mkd. in 1966, from which the remains of an original bearing tree:

A burned Oak stump, size indeterminate, bears S.27°E., 271 lks. dist., no marks visible.

and the remains of bearing trees mkd. by Gearhart in 1950:

A Fir stump 31" dia., bears N.56°E., 44 lks. dist., with healed blaze.

A Fir stump 33" dia., bears N.68°W., 28½ lks. dist., with healed blaze.

and a bearing tree mkd. by Jelley:

A Fir 32" dia., bears S.80½°E., 300 lks. dist., with healed blaze.

and new bearing trees;

A Cedar 9" dia., bears N.84½°E., 179 lks. dist. mkd. T29S R9W S25 BT.

A Fir 4" dia., bears S.79°W., 57 lks. dist. mkd. X BT.

A Fir 8" dia., bears N.86°W., 87 lks. dist. mkd. T29S R9W S26 BT.

FD. BC by D. Beedle, 10/2008 - 2008-0089