TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 23 and 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page 6618)

Set ¼ sec. post, from which
An Oak 15" dia., bears S.8°E., 1516 lks.
An Oak 15" dia., bears S.5°W., 1409 lks.

Arthur Boyer, Eng. #1581 - Wit: Bernard Denn; W.E. Howard; Leo Denn - Feb. 1955 - C.S. File 41/353; M 61-2

Searched diligently for witness trees without success, so set this corner midway between the SW. and the NW. corners of this section 24.
Drove a 3/4" x 36" Iron pipe at the corner. No trees nearby.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14008-09)

The ¼ sec. cor. determined at record bearing and distance from the original bearing trees:
A down Oak 25" dia., bears S.8°E., 1516 lks. dist., with scribe marks ¼ S visible on opened blaze.
An Oak 34" dia., bears S.5°W., 1409 lks., no marks visible
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: T 29 S R 9 W

¼
S 23 | S 24
1966

from which a new bearing tree
A Fir 6" dia., bears S.30½°E., 246 lks., mkd. ¼ S24 BT.
From this point, a fence corner bears S.86½°W., 0.34 chs. dist., with fence line extending N., S., and E.

BLM resurvey by A. Bert Skeesick Cadastral Surveyor under Group #2043, surveyed May/June 2003 - (DCSO rec. Vol. 55 Page(s) 21340)

The ¼ sec. cor. of secs. 23 & 24, monumented with an iron post, 2½" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.
from which the bearing tree mkd. by Jelley
A fir, 19" dia., bears S.30½°E., 162.4 ft., with a healed blaze.
No additional accessories available within limits.

Fd as per record 5/2019 by D. Edwards M175-61