TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 600440

PRIMARY CORNER DESCRIPTION 1/4 cor. for Secs. 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6619)

Marked a Fir 15" dia. for ¼ sec. cor., from which
A Fir 20' dia., bears S.22°E., 33 lks.
A Fir 15" dia., bears S.22°W., 34 lks.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14012)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: T 29 S R 9 W

¼
S 14 | S 13
1966

from which
A Fir 19" dia., bears N.6°E., 60 lks. dist. mkd.¼ S13 BT
A Fir 7" dia., bears S.75°W., 10½ lks. dist. mkd. ¼ S14 BT.

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2008, surveyed June/July 2002- (DCSO rec. Vol. 54 Page(s) 21056)

The ¼ sec. cor. of secs. 13 & 14, monumented with an iron post, 2½" dia., firmly set, projecting" above ground, with brass cap (properly) mkd.
from which the remains of bearing trees mkd. by Jelley
A fir, 31" dia., bears N.6°E., 39.6 ft., healed blaze.
A decayed sawed stump, 12" dia., species indeterminate, bears S.75°W., 6.9 ft., no marks visible. (Rec. fir)
and new bearing tree
A fir, 11" dia., bears N.75°W., 19.2 ft., mkd. ¼ S14 BT.

James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-18 A-C & revised map M166-43 C

Found - 3¼" brass cap stamped BLM 1966
BTs - 32" Fir with old tag N.10°E., 39.6'
11.5" Fir with healed face and tag dated 6/02, N.70°W., 19.2' to nail side center.

Fd ok by M. Erickson - 4/2019 - M171-58