

PRIMARY CORNER DESCRIPTION Sec Cor for 11, 12, 13 and 14


Alias	Description
Alias	Description
Alias	Description
Alias	Description

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6619)

-
- Set post cor. secs. 11, 12, 13 and 14, from which
- A Fir 12" dia., bears S.65°E., 25 lks.
 - A Fir 12" dia., bears S.40°W., 46 lks.
 - A Fir 24" dia., bears N.30°W., 55 lks.
 - A Laurel 6" dia., bears N.45°E., 54 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S. Bilow, crew - May 21, 1958 - C.S. File 49/7-1

Found - Orig. NW. BT, shows good bark scribing. Now snag.
All other orig. BTs would be in existing roadways.
Set Brass cap at cor. mkd: County Surveyors Office



- New BTs-
- 10" W.Fir bears S.63°E., 56.3 ft. scribed S13 T29S R9W CS BT.
 - 9" W.Fir bears S.31½°W., 133.3 ft. scribed S14 T29S R9W CS BT.
 - 8" W.Fir bears N.21½°W., 42.7 ft. scribed S11 T29S R9W CS BT.
 - 10" W.Fir bears N.48°E., 3.3 ft. scribed S12 T29S R9W CS BT.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14012-13)

The Sec. Cor., perpetuated and recorded by Byron in 1958, monumented with an iron pipe 1" dia., firmly set, extending 16" above the ground, with brass cap mkd. in 1958, from which the remaining original bearing tree

- A Fir snag 39" dia. bears N.30°W., 55 lks. dist., with scribe marks 29S 9W 11 visible on old bark blaze. This tree has been remarked T29S R9W S11 BT on bark blaze. and bearing trees marked by Byron
 - A W.Fir 15' dia., bears N.48°E., 5 lks. dist. with scribe marks T29S R9W S12 CS BT visible on partly healed double blaze.
 - A W.Fir 13" dia., bears S.63°E., 85 lks. dist., with healed double blaze.
- (Cont. Next Page)

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec Cor for 11, 12, 13 and 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

A W.Fir 25" dia., bears S.31½°W., 201 lks. dist., with
healed double blaze.
No bearing tree available to the NW. within limits.
Add BLM 1966 to brass cap.

Fd. OK, Jan. 1984 by E. Bloom - M 95-75
Fd. Ok by Greg Lang - 12/1998 - M 131-10
FD. ok by Greg Lang - 8/2006 2006-0095

BLM Dependent resurvey by A. Bert Skeesick, Cadastral
Surveyor & Robert H. Browning, Survey Tech under Group #2158,
surveyed April/May 2007 - (DCS0 records Vol. 55 Page(s)
21491-2)

The cor. of secs. 11, 12, 13, and 14, monumented with an iron
post, 1¼" dia., firmly set, projecting 13" above the ground,
with brass cap mkd.

COUNTY SURVEYORS

T 29 S

S 11 | S 12

S 14 | S 13

R9W BLM 1966

OFFICE 1958

from which the remains of an original bearing tree

A decayed fir stump, size indeterminate, bears N.30°W.,
36.3 ft., with fallen fir trunk, 36" dia., lying
alongside, with no marks visible.

and the remains of BTs mkd. by Byron, reported by Jelley

A fir, 20" dia., bears N.48°E., 3.3 ft., with a healed
double blaze.

A sawed, decayed fir stump, 18" dia., bears S.64¼°E., 56.1
ft., with no marks visible. (Record, S.63°E.)

and new bearing trees

A fir, 17" dia., bears S.41¾°E., 32.5 ft., mkd. T29S R9W
S13 BT.

A fir, 14" dia., bears S.81¼°W., 12.7 ft., mkd. T29S R9W
S14 BT.

A fir, 11" dia., bears N.59¼°W., 46.6 ft., mkd. T29S R9W
S11 BT.

Corner is located 1.0 ft. north of a 4-strand barbed wire
fence extending North and West.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail)
driven at the base right side-center, unless otherwise
described in the corner description

continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 600500

PRIMARY CORNER DESCRIPTION Sec Cor for 11, 12, 13 and 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

James Klein & Richard Kitz - For: Pacific Connector Gas Pipeline Project/Williams - Sept. 2014 - M166-18 A-C & revised map M166-43 C

Found - 2½" brass cap stamped County Surveyor 1958
BTs - 19.5" dead Fir with tag dated 1/63 N.45°E., 3.0'
15" Fir with healed face and tag dated 2007,
N.81°E., 12.7' to nail in side center, * record
S.81¼°W.
13" Fir with healed face and tag dated 2007,
S.59¼°E., 46.5' to nail in side center, * record
N.59¼°W.
15" Fir with healed face and tag dated 2007,
N.41¼°W., 32.5' to nail in side center, * record
S.41¼°E.
Note - * BLM 2007 record bearings.

Fd ok by M. Erickson - 4/2019 - M171-58