

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6620)

Set ¼ sec. post, from which
A Fir 15" dia., bears S.77°W., 36 lks.
A Fir 9" dia., bears N.78°E., 12 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; S.A. Bilow, crew - Sept. 1958 - C.S. File 49/100-24

Found - Orig. 9" now 30" W.Fir, N.78°E., 7.9 ft. I open near base, find good scribing "BT"
Orig. 15" now 30" Fir, down and partly rotted, checks bearing and distance, S.77°W., 23.8 ft.
Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 9 W
¼ S11|S12
1958

New BTs- 12" W.Fir bears S.64°W., 18.7 ft scribed ¼ S11 CS BT
12" W.Fir bears S.40½°E., 34.1 ft. scribed ¼ S12 CS BT.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14015)

(Found 1958 brass cap; 2 orig. BTs; 2 BTs by Byron)
"Add marks BLM 1966 to brass cap."

Fd. and Used in BLM Resurvey by Jack W. Bowder; John P. Farnsworth; Wayne L. Rogers, Cadastral Surveyors, Group #'s 976; #1000; #996; #1091, surveyed May 1979/Sept. 1982 - (DCSO records Vol. 44 Page(s) 17087)

Fd. Ok by Greg Lang - 12/1998 - M 131-10

BLM Dependent resurvey by A. Bert Skeesick, Cadastral Surveyor & Robert H. Browning, Survey Tech under Group #2158, surveyed April/May 2007 - (DCSO rec. Vol. 55 Pages 21492-3)

The ¼ sec. cor. of secs. 11 and 12, monumented with an iron post, 1¼ ins. diam., firmly set, projecting 14 ins. above the ground, with brass cap mkd. COUNTY SURVEYORS OFFICE
T 29 S R 9 W
1/4 S11| S12
1958 BLM1966

continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 600540

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 11 and 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

from which the remains of an original bearing tree
A sawed fir stump, 30" dia, bears N.78°E., 7.9 ft., with no marks visible.
and the remains of bearing trees mkd. by Byron, in 1958, reported by Bowder, Farnsworth, and Rogers
A sawed fir stump, 30" dia, bears S.40¼°E., 34.3 ft., with no marks visible. (Record, S.32°E.)
A fir snag, 18" dia, bears S.59½°W., 19.1 ft., with a healed double blaze.
and new bearing trees
A fir, 17" dia, bears N.80½°E., 30.8 ft., mkd. ¼ S12 BT
A fir, 30" dia, bears N.7¾°W., 29.2 ft., mkd. ¼ S11 BT.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center, unless otherwise described in the corner description

Fd. BC & 2 BTs, by Bartt Heichel 4/2025 - M184-77 A-B