

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1, 2, 11 and 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6620)

-
- Set post corner, secs. 1, 2, 11 and 12, from which
- A Fir 10" dia., bears S.4°E., 33 lks.
 - A Fir 12" dia., bears N.50°E., 28 lks.
 - A Fir 6" dia., bears N.30°W., 49 lks.
 - A Fir 18" dia., bears S.78°W., 38 lks.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14015-16)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 29 S R 9 W
 S 2 S 1
S 11 S 12
1966

- from which
- A Fir 16" dia., bears N.70°E., 64½ lks. dist. mkd. T29S R9W S1 BT.
 - A Fir 11" dia., bears S.54½°E., 78 lks. dist. mkd. T29S R9W S12 BT.
 - A Fir 10" dia., bears S.4°W., 55 lks. dist., mkd. T29S R9W S11 BT.
 - A Fir 15" dia., bears N.9½°W., 123 lks. dist., mkd. T29S R9W S2 BT.