

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 600640

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 2

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6621)

Set ¼ sec. post, from which
A Fir 20" dia., bears N.26°E., 52 lks.
A Fir 18" dia., bears N.26°W., 41 lks.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14017)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 23" in the ground, with brass cap mkd:
T 29 S R 9 W
¼
S2 S1
1966

from which
A Fir 8" dia., bears S.38°E., 28½ lks. dist., mkd. ¼ S1 BT.
A Fir 7" dia., bears N.51°W., 24 lks. dist., mkd. ¼ S2 BT.
Corner is located at the NE. cor. of logged area, edges bears generally S. and W.