

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 600700

PRIMARY CORNER DESCRIPTION Sec. Cor. for 1 & 2; 35 & 36, T28-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

**ON THE COUNTY LINE - CHECK WITH COOS COUNTY
FOR POSSIBLY MORE INFORMATION**

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6615)

Marked a Fir 36" dia., for cor. of secs. 1, 2, 35 and 36, from which

A Fir 50" dia., bears S.75°E., 13 lks.

A Fir 24" dia., bears S.89°W., 30 lks.

Only two BTs taken, as it was at first intended as an offset stand. Par.

BLM Resurvey by William W. Glenn, Cadastral Surveyor, under Group #'s 350 and 420, surveyed April/June 1959 - (DCSO records Vol. 30 Page(s) 12848)

Point for the sec. cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 28" long, 2 1/2" dia., 26" in the ground, with brass cap mkd:

T 28 S

R 9 W

S 35 S 36

S 2 S 1

T 29 S

1959

from which

A Fir 10" dia., bears N.45°E., 18 lks. dist. mkd. T28S R9W S36 BT.

A Fir 10" dia., bears S.45½°E., 49½ lks. dist. mkd. T29S R9W S1 BT.

A Fir 11" dia., bears S.77 3/4°W., 15 lks. dist. mkd. T29S R9W S2 BT.

A Fir 10" dia., bears N.23°W., 32 lks. dist. mkd. T28S R9W S35 BT.

Fd. and Used in BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14018)