

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCS0 records Vol. 16 Pg 6617)

Set ¼ sec. post, from which
 An Oak 30" dia., bears S.65°W., 412 lks.
 A Fir 40" dia., bears S.89°W., 758 lks.
No trees on N. side of line.

J. W. Cole, Deputy Co. Surveyor - Wit: P.D. Wolford; G.A. MacHenry - Aug/Sept. 1920 - Vol. 3 Page 70-71; C.S. File 6/17; Field book 48 Page 10+

Renew corner from remains of old BTs. Set Iron pipe 1½" dia., from which
 A Fir 26" dia., S.72½°W., 39 lks.
 A Fir 16" dia., N.7°15'E., 60 lks.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Oct. 16, 1959 - C.S. 49/100-69

Found - 1½" Iron pipe at corner and both BTs as recorded by Cole. The NE. now stump.
I do not set brass cap at corner.
New BT - 14" R.Fir bears N.5°E., 45.0 ft. scribed ¼ S25 CS BT.

Fd. OK, June 1984 by D. Stringer - M 97-4
Fd. OK, Feb. 1997 by D. Bentz - M 126-39

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff Lorsung- 10/1/2024 - C.S. File 67/59-1

Found - 1½" iron pipe projecting 5" and is 1 ft. NE from old fence cor. Fences run N-S and W.
26"x4 ft rotten shell of fir stump bears N.7°15'E. 39.60 (60 lks) scribe "¼" visible
Sawn, metal cap, 25"x 6 ft. D.Fir stump bears N.7°E. (rec. N.5°E) 45.0 ft. with fully healed double blaze.

New - A galvanized "U" post found on east edge of I.P.
At center of found I.P. drive 5/8"x30" I.R. w/2½" alum cap, marked as shown, protruding 11"

DOUGLAS COUNTY
T29S R9W
¼ S25
S36
2024
SURVEYORS OFFICE

cont next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 640200

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 25 and 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

New BTs- 13" K.M.X. Pine bears S.46°E., 35.0 ft. scribed "1/4 S36" "BT" on a double blaze.
9" D.Fir bears S.65°W., 17.6 ft. scribed "1/4 S36" "BT" on a double blaze.
7" I.Cedar bears N.36°W., 11.4 ft. scribed "1/4 S25" "BT" on a double blaze.

Note - Compass decl. 14¼°E.
Monument near bottom of very gentle north slope in old reprod forest.

Oregon Coordinate Reference System
Cottage Grove - Canyonville Zone
N 64973.294 E 62715.138

Fd DCSO Alum cap on IR - 10/2024 - D Edwards - M184-30