TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 640300

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 24 and 25

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6618)

Set ¼ sec. post, from which
An Ash 15" dia., bears N.89 3/4°E., 1827 lks.
An Ash 10" dia., bears S.88°E., 1912 lks.

J.W. Cole, Deputy Co. Surveyor - Wit: P.D. Wolford; G.A. MacHenry - Aug/Sept. 1920 - Vol. 3 Pages 70-71; Field Book 48 Page 10+; C.S. File 6/17

Set 1½" Iron pipe. No suitable trees near. Point checks from original BT which is dead but scribe marks still show.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14007-08)

The ¼ sec. cor., perpetuated and recorded by Cole on 1920, from an original bearing tree which is no longer in existence, monumented with an iron pipe 2" dia., firmly set, extending 2" above the ground.
At the corner point
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: T 29 S R 9 W
¼ S 24
S 25
1966
from which
A forked Ash 21" dia., bears N.2°E., 334 lks. dist. mkd. ¼ S24 BT.
No other bearing tree available within limits.
Reset iron pipe alongside the iron post.
Corner is located in a N. and S. fence line.

Fd BLM BC - 10/2024 - D Edwards - M184-30