

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6619)

Set ¼ sec. post, from which
A Fir 15" dia., bears S.67°W., 55 lks. dist.
A Fir 6" dia., bears N.10°W., 73 lks. dist.

Arthur Boyer, Eng. #1581 - Wit: Bernard Denn; W.E. Howard; Leo Denn - Feb. 1955 - C.S. File 41/353; M 61-2

The timber in the vicinity of a 500 ft. radius of where this corner should be, has been logged off so that there was nothing to indicate any sign of the witness trees: the distance between the NW. and the NE. is 5282.8 ft.

Set a 3/4" x 48" Iron pipe midway between section corners from which

A 9" W.Oak tree bears S.80½°E., 32.6 ft. mkd. ¼ S24 1581 BT.

34" Fir stump bears N.10½°E., 29.1 ft. mkd. ¼ S13 1581 BT.

Fd. IP & 2 BTs DCSO 10/1959 - C.S. File 49/100-66

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14010-11)

The ¼ sec. cor., reestablished at proportionate distance by Boyer in 1955, monumented with an iron pipe 3/4" dia., firmly set, extending 14" above the ground, from which bearing trees mkd. by Boyer:

A sawed Fir stump 34" dia., bears N.10½°E., 44 lks. dist., with scribe marks ¼ S13 BT visible on open blaze.

An Oak 10" dia., bears S.80½°E., 49 lks. dist., with healed double blaze.

At the corner point

Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd:

T 29 S R 9 W

¼ S 13

S 24

1966

from which a new bearing tree

A W.Fir 12" dia., bears N.64½°W., 57 lks. dist. mkd. ¼ S13 BT.

Reset iron pipe alongside the iron post.

continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 13 and 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2008, surveyed June/July 2002- (DCSO rec. Vol. 54 Page(s) 21053-4)

The ¼ sec. cor. of secs. 13 & 24, monumented with an iron post, 2½", firmly set, projecting 6" above ground, (with an iron pipe, 1" dia., projecting 14" above ground alongside), with brass cap (properly) mkd.

from which the remains of BTs mkd. by Boyer, Registered in 1955, and reported by Jelley

A decayed sawed stump, 34", species indeterminate, bears N.10½°E., 29.0 ft., with scribe marks ¼ S13 BT visible on open blaze. (Record, fir)

An oak, 12", bears S.80½°E., 32.3 ft., with healed blaze. and remains of a bearing tree mkd. by Jelley

A sawed fir stump, 21", bears N.64½°W., 37.6 ft., with healed blaze.

and new bearing tree

A fir, 6", bears N.29½°E., 26.3 ft., mkd. ¼ S13 BT.

Each new BT has a 2½"x¼" magnetic nail (MAG-NAIL) driven at the base on the right side-center, unless otherwise described in the corner description.