

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 640440

PRIMARY CORNER DESCRIPTION Center 1/4 Cor. Sec. 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2008, surveyed June/July 2002- (DCSO rec. Vol. 54 Page(s) 21058)

Point for the center $\frac{1}{4}$ sec. cor. of sec. 13, at the intersection with the E. and W. centerline.
Set a stainless steel post, 28" long, $2\frac{1}{2}$ " dia., 24" in the ground, with brass cap mkd. T 29 S R 9 W

C $\frac{1}{4}$
S 13
2002

from which

A cedar, 14" dia., bears N. $\frac{3}{4}$ °W., 27.8 ft., mkd. C $\frac{1}{4}$ S13 BT.

A fir, 6" dia., bears S.62 $\frac{1}{4}$ °E., 38.8 ft., mkd. C $\frac{1}{4}$ S13 BT.

Each new BT has a $2\frac{1}{2}$ "x $\frac{1}{4}$ " magnetic nail (MAG-NAIL) driven at the base on the right side-center, unless otherwise described in the corner description.

From this cor., an iron pipe, $\frac{3}{4}$ " dia., firmly set, projecting 2" above ground, with no cap, set by person(s) unknown, bears N.14°54'54"E., 4.22 ft. This point was not utilized in the course of this survey and was removed.

Deposit a magnet in a white plastic case at the base of the stainless steel post.