

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6620)

Set ¼ sec. post, from which
A Fir 12" dia., bears N.40°E., 24 lks. dist.
A Fir 24" dia., bears S.38°W., 20 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; C. Putnam, crew - Sept. 1959 - C.S. File 49/100-64

Found - Fir stump now 45", S.38°W., 13.2 ft. Chopped lower scar open and found scribe marks. Ring count proves this to be original BT.
Dead Fir, now 25", N.40°E., bark scribing "¼S", plainly visible. This tree also shows good lower scar.

(Line notes, including BTs for ¼ corner are recorded as line between secs. 13 and 24 in Co. Surveyors copy of govt. field notes.)

Set Brass cap at cor. mkd: County Surveyors Office
T 29 S R 9 W
¼ S 12
S 13
1959

Blaze and scribe new trees as follows:
8" Fir N.17½°W., 40.1 ft. scribed ¼ S12 CS BT.
9" Fir S.82°W., 42.6 ft. scribed ¼ S13 CS BT.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14013-14)

(Found 1959 brass cap, 2 orig. BTs.; 2 BTs by Byron)
"Add marks BLM 1966 to brass cap"

Fd. Ok by Greg Lang - 12/1998 - M 131-10

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #2008, surveyed June/July 2002- (DCSO rec. Vol. 54 Page(s) 21057)

The ¼ sec. cor. of secs. 12 and 13, monumented with an iron post, 1½" dia., firmly set, projecting 18" above ground, with brass cap (properly) mkd.
from which the remains of the original bearing trees

continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 640500

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 12 and 13

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A decayed sawed stump, 24" dia., species indeterminate, bears N.35°E., 16.5 ft. with scribe marks BT visible on open blaze. (Record, fir)
A decayed sawed stump, 31" dia., species indeterminate, bears S.38°W., 15.2 ft., with scribe marks BT visible on open blaze. (Record, fir)
and BTs mkd. by Byron, in 1959, and reported by Jelley
A fir, 22" dia., bears S.80½°W., 42.9 ft., with healed double blaze.
A fir, 19" dia., bears N.18½°W., 40.3 ft., with healed double blaze.
The cor. of fences extending N, E, & S, bears S.49°E., 4.7 ft
Fd. BC & 4 BTs, by Bartt Heichel 4/2025 - M184-77 A-B