TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 640600

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Secs. 1 and 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6621)

Set ¼ sec. post, from which
An Oak 12" dia., bears N.13°W., 75 lks.
An Oak 12" dia., bears S.20°W., 158 lks.

BLM resurvey by John Jelley, Cadastral Surveyor, Group #'s 350 & 606, surveyed Aug/Oct. 1966 - (DCSO records Vol. 34 Page(s) 14016-17)

Point for the ¼ sec. cor., at proportionate distance; there is no remaining evidence of the original corner.
Set an iron post, 28" long, 2 1/2" dia., 24" in the ground, with brass cap mkd: T 29 S R 9 W
¼ S 1 / S 12
1966
from which
A Fir 9" dia., bears N.75°W., 45½ lks. dist. mkd. ¼ S1 BT.
A Fir 11" dia., bears S.30°W., 11½ lks. dist. mkd. ¼ S12 BT.
Corner is located 1 lks. South of E. and W. fence.

Fd. Ok by Greg Lang - 12/1998 - M 131-10
Fd. BC & 2 BTs, by Bartt Heichel 4/2025 - M184-77 A-B