

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T29-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6575)

Set post, cor. secs. 30, 31, 25 and 36, from which
A W.Oak 36" dia., bears N.76°W., 372 lks. dist.
A W.Oak 12" dia., bears S.88°W, 319 lks. dist.
A W.Oak 6" dia., bears N.75°E., 86 lks. dist.
An Alder 20" dia., bears S.0°15'E., 597 lks. dist.

J.W. Cole, Deputy County Surveyor - Wit: P.D. Wolford; G.A. Mac Henry - Aug/Sept. 1920 - C.S. File 6/17; Field Book 48 Pg 10; Vol. 3 Pgs. 70-71

Drive Iron pipe 2" dia., 36" long, beside old corner stake, from which
A Stump of W.Oak N.75½°W., 382 lks.
Old BT, W.Oak N.75°E., 86 lks.
Old BT, W.Oak S.88°W., 319 lks.
No trace of other BT.

Survey by Bowker - Wit: Geo. Spaur; N.W. Chapman - March 2, 1926 - C.S. File 3/24 and ("old" corner book, Page 136)

Set 4" x 4" x 4 ft. post from one original BT which bears S.88°W., 319 lks. No other trees standing or near.

Douglas Co. Surveyors Office - James Byron, Deputy - John Powell, chairman - July 3, 1962 - C.S. File 49/139-90

Found - Orig. 36" now 40" W.Oak S.88°W., 210.5 ft. Old face rotted. No scribing found.
No other BTs found.

Statement filed in C.S. File signed by John R. Standley as follows: "I, John Standley, state that the BT used on this dte to renew this section corner is the original SW. BT that I have seen scribing on this W.Oak at various times during the past 40 years."

Set Brass cap at cor. mkd: County Surveyors Office 1962

T 29 S
R9W S 25 | S 30 R8W
S 36 | S 31

New BTs- 6" Ash bears N.5½°E., 43.0 ft. scribed S30 CSBT.
4" W.Oak bears N.21°W., 45.5 ft. scribed S25 CS BT
Rescribe orig. now 40" W.Oak "S36 T29S R9W CS BT"
50 ft. North to small creek.

This cor. is in old mill pond area. I.P. set at cor. not fd.

(Cont. Next Page)

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T29-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey by Donald Beck, Cadastral Surveyor, under Group #584 - Surveyed July 1965 - (DCSO records Vol. 33 Page 13883)

The Sec. Cor., perpetuated and recorded by Byron in 1962, monumented with an iron post, 1½" dia., firmly set, extending 14" above ground, with brass cap mkd. in 1962, from which the remains of the original SW. bearing tree:

An Oak snag 40" dia., bears S.86°W., 319 lks. dist., with no marks remaining on burned blaze, remarked S36 CS T29S R9W BT on double blaze, (Rec. S.88°W.)

and bearing trees mkd. by Byron:

An Ash 8" dia., bears N.3 ¾°E., 66 lks. dist., mkd. S30 CS BT on double blaze.

An oak 5" dia., bears N.23 ¾°W., 69 lks. dist. mkd. S25 CS BT on double blaze.

No suitable bearing trees available within limits in secs. 31 and 36.

Raise a mound of stone 3½ ft base, 3 ft high, W of the corner

Fd. OK, 1975 by OSHD - "N 8".

Fd. B.C., 1986 by OSHD - C.S. File 63/9-28

BLM resurvey by Wayne Rogers, Cadastral Surveyor and Robert Browning, Surveying Technician, under Group #1583 - Surveyed April/June 1991 - (DCSO records Vol. 49 Page(s) 18672-73)

The Sec. Cor., monumented with an iron post 1¼" dia., firmly set, projecting 18" above ground, with brass cap mkd. in 1962, from which the remains of an original bearing tree:

A decayed Oak snag 25" dia., bears S.86°W., 319 lks. dist., no marks visible.

and the remains of bearing trees mkd. by Byron in 1962,

An Ash stump 10" dia., bears N.3 ¾°E., 66 lks. dist., with healed double blaze.

An Oak 7" dia., bears N.23 ¾°W., 69 lks. dist. with healed double blaze.

and new bearing trees

A Fir 5" dia., bears N.66¾°E., 6 lks. mkd. T29S R8W S30 BT

A Fir 6" dia. bears S.40¾°E., 250 lks mkd. T29S R8W S31 BT

A Pine 10" dia. bears S.65¼°W. 87 lks mkd. T29S R9W S36 BT

This corner is located at base of dike of old log pond.

Fd. IP w/BC - James M. Standley - For: ODOT - 12/2007 - St. Hwy 42-013A

Fd. as per 1991 BLM survey by D. Edwards Dec. 2012, M165-31

continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 700200

PRIMARY CORNER DESCRIPTION Sec. Cor. for 25 & 36; 30 & 31, T29-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

David Edwards - For: Pete & Bonnie Dancer - 10/2024 - M184-30

Found - DCS0 brass cap
An 18" dia. fir w/HB bears N.66 $\frac{3}{4}$ °E., 4.0'
A 10" dia. oak w/HB bears N.23 $\frac{3}{4}$ °W., 45.5'
All other BT's gone.
No trees available to the south