

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T29-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GL0 survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 16 Page(s) 6574)

Set post, cor. sec. 19, 30, 24 and 25, from which
An Ash 15" dia., bears N.36°E., 1049 lks. dist.
An Ash 12" dia., bears S.62°E., 974 lks. dist.
An Ash 12" dia., bears N.1°W., 1075 lks. dist.
An Ash 12" dia., bears N.86½°W., 1272 lks. dist.

J.W. Cole, Deputy - Wit: P.D. Wolford; G.A. Mac Henry - For: Denn Estate - Sept. 1920 - C.S. File 6/17; Field Book 48 Pg. 10; Vol. 3 Pg. 70-71

Rock, buried beneath surface, containing 2,000 cubic inches, mkd. with X on top. Remains of old BT to NE.

Arthur Boyer, Eng. #1581 - Wit: Bernard Denn; W.E. Howard; Leo Denn - Feb. 8, 1955 - C.S. File 41/353A & M 61-2

Found rock with cross on top, 18" below ground surface on the East should of county road.
Set a 1/2" Iron pipe, 18" long on top of this cross, on rock, which is 13 ft. West of the East side of road as fenced and it is 247.5 ft. South of a 1/2" x 30" iron pipe which is driven in the fence on the East side of road. This 1/2" x 30" I.P. is in line with a fence that runs West from the road.

Survey by Herbert Northcraft - For: James Atterberry - July/Aug. 1976 - M 61-18

Set 1/2" x 10" R.R. Spike in black top. Set 5/8" x 42" I.R. at right angles to section line.

Douglas Co. Surveyors Office - Randall Smith & Stephen Flause - C.S. 64/78-2 - Sept. 18, 97

Mon. FD. - Strong sound with metal locator. Note: Corner is a rock in 1920 & 1955, in 1976 corner is a R.R. spike in black top.

Asphalt not dug up.

Accessories Fd. -

3/4" iron pipe, bears N.75 3/4°W., 987.3' (rec. N.75 3/4°W., 986.8') per M 61-2.

5/8" iron rod in east r/w fence, bears N.3°E., 247.8' (agrees with rec. To a 1/2" I.P. per M 61-2).

(Cont. Next page)

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 700300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 24 & 25; 19 & 30, T29-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

5/8" iron rod in west R/W fence, bears N.5
3/4^oW., 248.9' (rec. To a 1/2" I.P. per M 61-2
is N.5 3/4^oW., 248.5').

5/8" Iron rod in east R/W fence, bears east 13'
(agrees with rec.) M 61-80.

5/8" iron rod in west R/W fence, bears west
28.4' (agrees with rec.) M 61-80.

New Accessories -
SE corner of small blue colored shop, bears
N.64^oW., 300.5'.