

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1 (NE Tsp. Cor)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

ON THE COUNTY LINE - CHECK WITH COOS COUNTY
FOR POSSIBLY MORE INFORMATION

GLO survey by Dennis Hathorn, Deputy Surveyor under Contract #57, dated April 12, 1855 - (DCSO records Vol. 14 Page(s) 5788)

Set post cor. Tps. 28 and 29 and South R's 8 and 9 West, from which

- A Fir 12" dia., bears N.74°E., 27 lks. dist.
- A Fir 15" dia., bears S.60°E., 21 lks. dist.
- A Fir 15" dia., bears N.86½°W., 36 lks. dist.
- An Alder 15" dia., bears S.30°W., 69 lks. dist.

Douglas Co. Surveyors Office - James Byron, Deputy - Milo Godfrey; crew - Sept. 10, 1957 - C.S. File 49/12-12

Found - 3/4" Iron pipe at corner.
Orig. BT, 15" now 24" rotted stump, N.86½°W., 23.8 ft. Good scribing on chip of old face.

This corner renewed by Coos Head Timber Co., Aug. 1956 per notes on yellow tag. Original BT checks bearing and distance to 3/4" I.P.

I find these BTs scribed in 1956:

- 7" R.Fir S.8°W., 22.8 ft. scribed BT S1 T29S R9W
- 6" R.Fir N.76½°E., 21.0 ft. scribed BT S31 T28S R8W.
- 24" Cedar N.3°E., 86.9 ft. scribed BT S31 T28S R8W.

BLM resurvey by William W. Glenn, Cadastral Surveyor, under Group's #350 and 420, Surveyed April/June 1959 - (DCSO records Vol. 30 Page(s) 12846-47)

At the Tps. Corner, recorded by Byron in 1957, previously perpetuated with an iron pipe, 3/4" dia., firmly set, 14" above ground, from which the remaining original bearing trees:

A sawed and rotted Fir stump 24" dia., bears N.86½°W., 36 lks. dist., with scribe marks S 8 W visible on chop of old face.

and locally established bearing trees:

- A Cedar 24" dia., bears N.1 3/4°E., 131½ lks. dist. mkd. BT S31 R8W T28S.
- A Fir 6" dia., bears N.76°E., 32 lks. dist. mkd. BT S31 R8W.
- A Fir 7" dia., bears S.6½°W., 34½ lks. dist. mkd. BT S1 T29S R9W.

At the corner point

(Cont. Next Page)

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1 (NE Tsp. Cor.)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set an iron post, 28" long, 2½" dia., 26" in the ground, with brass cap mkd:

T 28 S	
R 9 W	R 8 W
S 36	S 31
S 1	S 6
T 29 S	
1959	

from which

A Fir 7" dia., bears S.43½°E., 56 lks. dist., mkd. T29S R8W S6 BT.

A Maple 5" dia., bears N.52½°W., 65 lks. dist. mkd. T28S R9W S36 BT.

Deposit iron pipe alongside iron post.

BLM resurvey by John Jelley, Cadastral Surveyor, Group # 552, surveyed July 1964 - (DCS0 records Vol. 32 Page(s) 13569-70)

The Tps. corner, monumented with an iron post, 2½" dia., 2" above ground, firmly set, with brass cap mkd. in 1959, from which local bearing trees:

A sawed Cedar stump 24" dia., bears N.1 3/4°E., 131½ lks. dist., no marks remain.

A Fir 7" dia., bears N.76°E., 32 lks. dist. with fragmentary scribe marks visible on partially healed blaze.

A Fir 8" dia., bears S.6½°W., 34½ lks. dist., with fragmentary scribe marks visible on partially healed blaze. and a bearing tree mkd. by Glenn, in 1959

A Fir 8" dia., bears S.43½°E., 56 lks. dist., with fragmentary scribe marks visible on partially healed blaze.

from which a new bearing tree:

A White Fir 12" dia., bears N.73°W., 248 lks. dist. mkd. T28S R9W S36 BT.

Fd. OK by K. Hoffine, Nov. 1999 - M133-58

Douglas Co. Surveyors Office - Crew: Stephen J Flause & Jeff Lorsung - Nov. 15, 2018 (Filed 11/17/2021) - C.S. 67/50-6

Found - A 2½" o.d. iron pipe, firmly set, projecting 6" above the ground with a 3¼" dia. brass cap (properly) marked

BTs by Byron in 1957 -

A very rotted 14"x1.5 tall cedar stump bears N.1°E., 86.9 ft. (No blaze evidence)

A 34" dia. D.Fir bears N.74½°E., 21 ft with a fully healed blaze.

A 40" diam. D.Fir bears S.6½°W., 22.8 ft with a fully healed blaze. Continued next page

TOWNSHIP 29 RANGE 09 POINT IDENTIFIER # 700700

PRIMARY CORNER DESCRIPTION NE Cor. Sec. 1 (NE Tsp. Cor)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

BTs by Jelley for BLM in 1964 -
A 24"x3' tall sawn grand fir stump bears N.73°W.,
163.7 ft. (tipped out - Measurement was to center
root hole)
New - A 6" dia. G.Fir bears S.81°W., 17.4 ft scribed "X",
"BT" on a double blaze.
A 3" dia. maple bears N.7½°W., 13.15 ft scribed "X"
"BT" on a double blaze.
Note - The corner falls on flat ground in mixed fir and
maple forest. The monument lies 1.5 ft. North of
a fence corner with fences running South and
East.
All BTs have BT Tags attached. All new BTs have
double blazed faces with bearing measured to the
center of the trees at the root crown and
distances measured to a 4" mag nail in the side
and center of the root crown.
GEODETIC COORDINATES
LAT: 43°05'00.437765080"N LONG: 123°42'07.696406340"E
NAD 83 - GeoXT6000 - OREGON SOUTH-ZONE3602
Compass declination: 15°E.