

PRIMARY CORNER DESCRIPTION S.W. Township Cor.

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Original - Dennis Hathorn, Deputy, Contract #57 dated April 12, 1855 (DCSO records, Vol. 16 Page 6572)

Set post, cor. Tp. 29 & 30 S., and R's 7 & 8 W, from which;
A Fir, 12" dia., bears N.24°W., 38 lks.
A Fir, 12" dia., bears N.34°E., 25 lks.
A Fir, 12" dia., bears S.48°E., 20 lks.
A Fir, 15" dia., bears S.1°W., 19 lks.

Re-establishment of corners - Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Pages 6021-22)

Intersect the point for the Hathorn cor. of Tps. 29 & 30 S., R 7 & 8 W., located by measurement from the SW orig. bearing tree and from the position indicated by stump holes of the NE., NW., and SE., bearing trees, all of which have been destroyed by decay.

At the exact cor. point
Set and iron post, 3' long, 3" dia., 27" in the ground, for cor. of T29S R8W & T29½S R7W, with brass cap mkd:

T29S	T29½S
R8W	R7W
<u>S36</u>	<u>S31</u>
1924	

from which

A Fir, 30" dia., bears N.59°E., 50 lks. mkd: T29½S R7W S31
BT.

A Fir, 24" dia., bears N.4°W., 41 lks. mkd: T29S R8W S36
BT.

Orig. SW bearing tree, a Fir, 24", bears S.1°W., 19 lks. marks have been obliterated by Deputy Byars.

Douglas Co. Surveyors Office - James W. Byron, Deputy & Crew - June 1962 - C.S. 49/139-84

Found - Brass cap at cor. & both BTs. NE BT, now stump, shows scribing. We open NW BT & find good scribing.

New BTs- 13" R. Fir, bears N.15°E., 33.7' scribed T29½S R7W S31 CS BT.

8" W. Fir, bears S.72°W., 37.1' scribed T30S R7W S6 CS BT.

continued next page

PRIMARY CORNER DESCRIPTION S.W. Township Cor.

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

BLM rehabilitation of certain corners, A. Bert Skeesick, Cadastral Surveyor, under Group #2000, Surveyed Sept. 2002, - (DCSO records Vol. 54 Page(s) 21137-8)

The cor. of Tps. 29 & 29½ S., Rs. 7 & 8 W., monumented with an iron post, 3" dia., firmly set, flush with the ground, with brass cap (properly) mkd.

from which the remains of an orig. bearing tree

A sawed & decayed fir stump, 27" dia., bears S.1°W., 12.5 ft., with healed blaze. (The marks had been obliterated by William. H. Byars, U.S. Deputy Surveyor, in 1883.)

and the remains of bearing trees mkd. by Mensch

A decayed stump, size and species indeterminate, bears N.59°E., 33.0 ft. with no marks visible. (Record, fir)

A fir snag, 29" dia., bears N.4°W., 27.1 ft., with no scribe marks visible on opened blaze.

and the remains of bearing trees mkd. by the Douglas County Surveyor's Office, in 1962

A fir snag, 15" dia., bears N.15°E., 33.7 ft., with scribe marks ½ SR7W S31 CS BT visible on partially healed double blaze.

A fir, 23" dia., bears S.72°W., 37.1 ft., with healed double blaze.

and new bearing trees

A fir, 20" dia., bears N.45°E., 22.8 ft., mkd. T29½S R7W S31 BT.

A fir, 10" dia., bears N.59½°W., 9.2 ft., mkd. T29S R8W S36 BT.

Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

The geographic position (NAD 1983) of this cor. as determined by a differentially corrected, mapping grade GPS receiver, (Trimble GEO Explorer 3), observation, is as follows:

Latitude: 42°59'50.87"North, Longitude: 123°34'59.06" West