

TOWNSHIP 29<sup>1/2</sup> RANGE 07 POINT IDENTIFIER # 134200

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. Sec. 31 Only, T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6522)

-----  
Set  $\frac{1}{4}$  sec. post, at proper dist. from which;  
A Laurel, 20" dia., bears S.30°E., 100 lks.  
A Laurel, 12" dia., bears N.50°W., 50 lks.

Re-establishment of corners - Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6037)

-----  
Proportionate distance.  
Set an iron post, 3' long, 1" dia., 28" in the ground, for  $\frac{1}{4}$  sec. cor. of sec. 31 only, with brass cap mkd:

$\frac{1}{4}$  S31  
1924

from which

A Fir, 20" dia., bears N.60°E., 45 lks. mkd.  $\frac{1}{4}$  S31 BT.  
A Fir, 18" dia., bears N.68°W., 76 lks. mkd.  $\frac{1}{4}$  S31 BT.