

TOWNSHIP 29½ RANGE 07 POINT IDENTIFIER # 172200

PRIMARY CORNER DESCRIPTION S. Sec. Cor 31 & 32 Only T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6522)

-----  
Set a post, at proper distance, cor. of secs. 5, 6, 31 & 32 from which;

- A Red Fir, 20" dia., bears N.55°W., 10 lks.
- A Red Fir, 4" dia., bears N.50°E., 26 lks.
- A Red Fir, 30" dia., bears S.55°E., 17 lks.
- A Chinquapin, 5" dia., bears S.25°W., 43 lks.

Re-establishment of corners - Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Pg. 6038)

-----  
Intersect the point for cor. of secs. 5, 6, 31 & 32, located by measurement from the orig. bearing trees.

At the exact cor. point

Set an iron post, 3' long, 2" dia., 28" in the ground, for cor. of secs. 31 & 32, with brass cap mkd:

T29S	R7W
S31	S32
-----	
1924	

from which (the orig. bearing trees)

- A Fir, 14" dia., bears N.53°E., 26 lks. (not N.50°E.) marks grown over and not opened.
- A Fir, 36" dia, bears S.55°E., 17 lks. marks have been obliterated.
- A Chinquapin, 12" dia., bears S.18°W., 38 lks. (not S.25°W. 43 lks.) marks have been obliterated.
- A Fir, 30" dia., bears N.55°W., 10 lks. marks have been obliterated.

New bearing trees:

- A Fir, 12" dia., bears N.70°E., 82 lks. mkd: T29S R7W S32 BT.
- A Maple, 12' dia., bears N.4½°W., 43 lks. mkd: T29S R7W S31 BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland - John Powell - May 1962 - C.S. File 49/139

-----  
Found - Brass cap at cor.

12", now 20" Fir, N.70°E., 54.1' alive & in good condition.

12", now 18' Maple N.4½°W., 28.4', center rotted. I rescribe this BT S 31 CS BT.

(Cont. Next Page)

TOWNSHIP 29½ RANGE 07 POINT IDENTIFIER # 172200

PRIMARY CORNER DESCRIPTION S. Sec. Cor. 31 & 32 Only, T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM resurvey, by Boyd W. Peterson, under special instructions dated August 8, 1988. Surveyed Sept./Dec. 1988 (DCSO records Vol. 49 Page(s) 18816-17)

-----  
The cor. of secs. 31 & 32 only, T29S R7W, monumented with an iron post, 2" dia., firmly set, projecting 12" above ground, with brass cap mkd:

T29S R7W  
S 31 | S 32  
-----  
1924

from which the only remaining bearing tree mkd. by Mensch  
A White Fir, 31" dia., bears N.70°E., 82 lks., with healed blaze.

No other suitable trees available.

Ted Baker, Roberts Surveying - For: Seneca Jones Timber Co. - Oct. 2000 - M 136-9 A & B

-----  
Found - 1924 GLO Brass cap.  
32" W.Fir, N.70°E., 54.1 ft. (scar vis)  
New BT - 5" Fir, N.30°W., 15.4 ft.  
Note - All new BTs are scribed & painted red. Distances to BTs are center measured.

BLM resurvey by A. Bert Skeesick, Cadastral Surveyor under Group #1000, surveyed Jan. 2002 - (DCSO rec. Vol. 53 Page(s) 20727-8)

-----  
The cor. of secs. 31 and 32 only, perpetuated by Baker, in 2000, monumented with an iron post, 2" diam., firmly set, projecting 11" above ground, with brass cap (properly) mkd. from which the remains of a bearing tree mkd. by Mensch

A sawed fir stump, 34" dia., bears N.70°E., 54.1 ft., with a healed blaze.  
and bearing tree mkd. by Baker

A fir, 6" dia., bears N.36°W., 15.4 ft., with scribe marks  
BT visible on partially opened blaze.  
and new accessory

An aluminum rod, 36" long, ¾" dia., driven 33" in the ground for a reference monument, bears N.87°E., 38.8 ft., with brass cap mkd. RM T29S R7W S32 38.8 FT TO COR 2002 and an arrow pointing to the corner.  
Drive a steel fencepost alongside cor.