

TOWNSHIP 29½ RANGE 07 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Closing Cor. 31 & 32 Only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Orig. (Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Pages 6055-56)

Intersect the S. bdy. of T29S R7W, 7.64 chs. N.88°12'E., from the cor. of secs. 31 & 32.
At the point of intersection
Set an iron post, 3' long, 2" dia., 28" in the ground, for cor. of secs. 31 & 32, with brass cap mkd:

S31 | S32
T29½S | R7W
1924

from which;
A Dogwood, 7" dia., bears S.65°E., 34 lks. mkd: T29½S R7W S32 BT.
A Fir, 10" dia., bears S.53°W., 41 lks. mkd: T29½S R7W S31 BT.

Douglas Co. Surveyors Office - James Byron, Deputy - Dale McFarland - John Powell - May 1962 - C.S. File 49/139-68

Found - 10", now down 14" Fir, S.53°W., 27.1', shows good scribing "S".
Dogwood to SE not found but we do find 12" Yewwood, checks bearing & dist. to SE BT.
Note - Brass cap set for corner not found. Falls in old cat road & about 10' south of creek channel.
New BTs- 12" Yewwood bears S.66°E., 23.2', scribed S32 T29½S R7W CS BT.
18" W. Fir, bears S.81½°W., 79.7', scribed S31 T29½S R7W CS BT.

BLM resurvey, by Boyd W. Peterson, under special instructions dated August 8, 1988. Under Group #1456 Surveyed Sept./Dec. 1988 (DCSO records Vol. 49 Page(s) 18820-21)

True point for the closing cor. of secs. 31 & 32, at intersection with the S. bdy. of T.29S. R.7W.
Set a stainless steel post, 28" long, 2½" diam., 22" in the ground, with brass cap mkd: T29S R7W

S32
S31 | S32
C C
T29½S R7W

1988
from which
A Fir, 8" dia., bears S.84°E., 21 lks. mkd: T29½S R7W S32 CC BT.
(Cont. Next Page)

TOWNSHIP 29½ RANGE 07 POINT IDENTIFIER # 200200

PRIMARY CORNER DESCRIPTION Closing Cor. Sec. 31 & 32 Only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir, 7" dia., bears S.17°W., 27 lks. dist., mkd: T29½S R7W S31 CC BT.
Deposit white "DEEP-1" magnetic marker at base of stainless steel post.
From this point, the original closing cor. of secs. 31 & 32 perpetuated and recorded by Byron, DCSO deputy, in 1962 bears N.0°02'30"W., 0.070 chs. monumented with an iron post, 1¼" dia., firmly set flush with the ground, with brass cap mkd: COUNTY SURVEYORS OFFICE T29½S R7W S31 32 1962, from which the remains of an orig. bearing tree:
A root hole, bears S.53°W., 41 lks. with a down and rotted Fir alongside, 12" dia., no marks visible on rotted blaze.
and a bearing tree mkd. by Byron
A yew, 22" dia., bears S.66°E., 35 lks. dist. with fragmentary scribe marks visible on partially healed blaze.
and a new bearing tree
A Fir, 8" dia., bears S.77°W., 16 lks. dist., mkd: T29½S R7W S31 BT.
From this same point, the cor. of secs. 31 & 32 only, T29S R7W, bears S.88°16'30"W., 7.685 chs.

Found OK by T. Baker, Oct. 2000 - M136-9 A&B