

TOWNSHIP 29½ RANGE 07 POINT IDENTIFIER # 232200

PRIMARY CORNER DESCRIPTION S. 1/4 Cor. Sec. 32 Only T29-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - Nathaniel Ford, under Contract #44 dated May 30, 1854 (DCSO records, Vol. 15 Page 6522)

Set ¼ sec. post, at proper distance from which;
A B. Oak, 15" dia., bears N.50°W., 25 lks.
A Red Fir, 30" dia., bears S.80°W., 75 lks.

Re-establishment of corners - Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6039)

Intersect the point for ¼ sec. cor., located by measurement from the orig. bearing trees.
At the exact cor. point
Set an iron post, 3' long, 1" dia, 28" in the ground, for ¼ sec. cor. of sec. 32 only, with brass cap mkd:
¼ S32
1924
from which (the orig. bearing trees)
A Black Oak, 24" dia., bears N.34°W., 25 lks. (not N.50°W.) marks show on the overgrowth.
A Fir stump, bears S.81°W., 75 lks. (not S.80°W.)
New bearing trees
A Fir, 6" dia., bears N.38°E., 13 lks. mkd: ¼ S32 BT.
A Fir, 8" dia., bears N.14°W., 20 lks. mkd: ¼ S32 BT.

Douglas Co. Surveyors Office - Ben B. Irving, Co. Surveyor - James Byron - Ray Irving - Work done under order of County Court - Feb. 1954 - C.S. File 46/36

Corner positively identified. Brass cap at corner and 6" Red Fir, N.38°E., 13 lks. standing.
Blazed and scribed 2 trees:
8" Red Fir, N.28°W., 4.4', mkd: T29S ¼ S32 CS BT
10" Red Fir, N.51.°E., 12.0', mkd: T29S ¼ S32 CS BT

Douglas Co. Surveyors Office - James W. Byron, Deputy & Crew - June 1962 - C.S. File 49/139-80

Found - Brass Cap set in 1924 & BT as follows:
8" R. Fir, scribed by B. Irving in 1954, now 5' snag, scribing vis.
10" R. Fir, N.51°E., 12.0' OK
New BT - 7" R. Fir, N.62°W., 20.8' scribed S¼ S32 CS BT.

FD Ok by BLM resurvey DCSO records Vol 49 Pages 18815-16

Found OK by T. Baker, Oct. 2000 - M136-9 A&B