

TOWNSHIP 29½ RANGE 07 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Cor. Secs. 32 & 33 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Orig. (Corrective resurvey)- Fred Mensch, U.S. Deputy Surveyor - under date of April 18, 1924 (DCSO Vol. 14 Page 6055)

Intersect the S. bdy. of T29S R7W, 8.7 chs. S.89°25'E., from the cor. of secs. 32 & 33.

At the point of intersection

Set an iron post, 3' long, 2" diam., 28" in the ground, with brass cap mkd:

S 32 S 33
T29½S R7W
1924

from which

A Fir, 28" dia., bears S.30°E., 50 lks., mkd. T29½S R7W S33 BT.

A Maple, 8" dia, bears S.29°W., 52 lks., mkd. T29½S R7W S32 BT.

BLM resurvey by Harvey Wofford, G. Steven Popken, & James J. Carlson, instructions dated August 29, 1974, under Group #851. Surveyed Sept. 1974/May 1976. (DCSO records Vol. 39 Pages 15816-17)

The cor. of secs. 32 & 33 only, on the N. bdy of T29½S R7W monumented with an iron post, 2" dia., firmly set, projecting 6" above ground, with brass cap mkd:

S 32 S 33
T 29½ S R 7 W
1924

from which the remains of the orig. bearing trees

A Fir, 42" dia, bears S.30°E., 50 lks., with healed blaze.

A Maple snag, 9" dia., bears S.29°W., 52 lks., with scribe marks T29½S R7W S32 BT visible on open blaze.

and a bearing tree of no record

A Fir, 62" dia., bears S.63°W., 24 lks., with healed blaze.

FD OK -BLM resurvey, by Boyd W. Peterson, under special instructions dated August 8, 1988. Under Group #1456 Surveyed Sept./Dec. 1988 (DCSO records Vol. 49 Pages 18819-20)

Found OK by T. Baker, Oct. 2000 - M136-9 A&B