

TOWNSHIP 29½ RANGE 07 POINT IDENTIFIER # 340100

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 33; & S 4, T30-7

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Original - W.H. Byars, under contract # 456 dated July. 28, 1882 (DCSO rec. Vol. 15 Pg. 6551)

Set a stone 14 x 12 x 10 ins., 8" in ground for the ¼ sec. corner, marked ¼ on the North side and from which
A Laurel 12" dia., bears S.19°E., 66 lks. dist. marked ¼ S, BT.
A Laurel 12" dia., bears N.51°W., 64 lks. dist., marked ¼ S, BT.

GL0 survey by Mensch under Instructions dated April 18, 1924 (DCSO records Vol. 14 Page(s) 6051)

Intersect the ¼ sec. cor., which is a slate stone, 4 x 10 x 10 ins. above ground, firmly set, marked ¼ on N. face; from which the original bearing trees:
A Laurel 18" dia., bears S.19°E., 66 lks. dist., marked ¼ S BT.
A Laurel 20" dia., bears N.51°W., 64 lks. dist., marked ¼ S BT. I re-mark this tree ¼ S 33 T29½ BT.

Douglas Co. Surveyors Office - James W. Byron, Deputy - Dale McFarland; John Powell - June 1962 - C.S. File 49/139-87

Found - Stone and both BTs as recorded. BTs now have rotted faces.
New BTs -6" R.Fir bears S.35°E., 8.0 ft. scribed ¼ S4 CS BT.
7" Laurel bears N.17°E., 16.4 ft. scribed ¼ S33 CS BT.

Howard Johnstone - For: Roseburg Lumber Co. - June 29, 1984 - M 97-14

Found - Rock, 8" x 6" x 4", exposed, marked "¼".
24" Madrone N.51°W., 42.2 ft. rotted face.
9" Fir S.35°E., 8.0 ft. healed.
19" Madrone S.19°E., 43.6 ft. healed.
10" Madrone N.17°E., 16.4 ft. scribe visible.
Set 5/8" x 48" Iron rod and alum. cap alongside rock. Cap marked with "LS 498".