

TOWNSHIP 29½ RANGE 07 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION No. ¼ cor. for Sec. 34 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Mensch under Instructions dated April 18, 1924  
(DCSO records Vol. 14 Page(s) 6044)

-----  
Point for ¼ sec. cor. of sec. 34 only, T29½S R7W, later  
determined.

Set an Iron post, 3 ft. long, 1" dia., 28" in the ground, for  
¼ sec. cor. of sec. 34, T29½S R7W., only with brass cap mkd:

-----  
¼ S34  
T29½  
1924

from which

A Laurel 44" dia., bears S.3°E., 62 lks. dist., marked ¼  
S34 T29½ BT.

A Laurel 46" dia., bears S.54°W., 58 lks. dist., marked ¼  
S34 T29½ BT.

BLM survey by Wofford, Popken and Carlson, under Group #851.  
Surveyed Sept. 1974/May 1976 (DCSO records Vol. 39 Page(s)  
15813-14)

-----  
True point for the ¼ sec. cor. of sec. 34 only, on the N.  
bdy. of T29½S R7W.

Set an iron post 28" long, 2½" dia., 22" in the ground, with  
brass cap mkd:

-----  
¼ S 34  
T 29½ S R 7 W  
1976

from which

A Pine 34" dia., bears S.72½°E., 29 lks. dist., mkd. ¼ S34  
BT.

From this point, the orig. ¼ sec. cor. of sec. 34, bears  
South, 0.084 chs. dist., monumented with an iron post, 1"  
dia., firmly set, projecting 8" above ground, with brass cap  
marked:

-----  
¼ S 34  
1924  
T 29½

from which the original bearing trees:

A Madrone 46" dia., bears S.3°E., 62 lks. dist., with  
healed blaze.

A Madrone 62" dia., bears S.54°W., 61 lks. dist., with  
healed blaze.

I add marks AM 1976.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION No. ¼ Cor. for Sec. 34 only

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Howard Johnstone, For: Roseburg Lumber Co. - July 30, 1980 -  
M 84-80 and C.S. File 58/214-2

-----  
Found - 1924 GLO brass cap and iron pipe mkd. "AM 1976".  
1976 Cadastral brass cap and iron pipe bears  
N.5°52'33"W., 5.23 ft.  
Set 5/8" x 40" I.R. and al. cap 8.69 ft. South of 1924 BC/IP.  
New BTs -36" Pine, N.66°E., 19.0 ft.  
66" Madrone S.66°W., 35.0 ft.

Howard Johnstone, For: Roseburg Lumber Co. - Jan. 22, 1981 -  
C.S. File 58/229-7

-----  
Scribed new bearing tree for North ¼ corner, Sec. 34, T29½S  
R7W because new road construction will eliminate O.B.T., 66"  
madrone, S.66°W., 35.0 ft.  
Found - 1924 GLO BC/IP marked "AM 1976".  
Our 5/8" x 40" I.R. and alum. cap 8.69 ft. South of  
BC and on true line.  
36" Pine, N.66°E., 19.0 ft.  
66" madrone S.66°W., 35.0 ft.  
New BT - 11" D.Fir S.56°E., 60.2 ft. from alum. cap (S.48°E.,  
64.6 ft. from GLO brass cap.

BLM Corrective dependent resurvey by Jelley and Rogers, under  
Group #851, Surveyed, Jan. 1981 (DCSO records Vol. 42 Page(s)  
16425)

-----  
The ¼ sec. cor. of sec. 34 only, on the N. bdy. of T29½S R7W,  
established and recorded by Howard Johnstone in 1980, and is  
accepted as the corner, monumented with an iron rod, 5/8"  
dia., firmly set, projecting 10" above ground with an alum.  
cap 2" dia., mkd.: T 29 ½ S R 7 W S34 ONLY

N 1/4  
1980  
LS 498

from which a bearing tree mkd. by Johnstone:  
A Fir 10" dia., bears S.60°E., 91 lks. dist., with scribe  
marks ¼ S34 BT visible on open blaze.  
and a new bearing tree:  
A Fir 18" dia., bears S.75°W., 132 lks. mkd. ¼ S34  
BT.

From this point, the orig. ¼ sec. cor. of sec. 34 bears  
North, 0.131 chs. dist., monumented with an iron post, 1"  
dia., firmly set, projecting 8" above ground, with brass cap  
marked:

(Cont. Next Page)

TOWNSHIP 29½ RANGE 07 POINT IDENTIFIER # 440200

PRIMARY CORNER DESCRIPTION No. ¼ Cor. for Sec. 34 only

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

AM  
¼ S 34  
T 29 ½ S  
1976  
1924

from which the original bearing trees:

A Madrone 50" dia., bears S.3°E., 62 lks. dist., with healed blaze.

A madrone 64" dia., bears S.54°W., 61 lks. dist., with healed blaze.

From this same point, the ¼ sec. cor. of sec. 34 only, erroneously established by Wofford, Popken and Carlson, in 1974-76, bears N.2°12'W., 0.208 chs. dist., monumented with an iron post, 2½" dia., firmly set, projecting 6" above ground, mkd. and witnessed as described in the official record.

I remove the iron post and destroy the marks on the bearing trees.